



Information & Requirements *for* Electric Supply below 600 volts

2008 Edition

This publication
supersedes similar publications
previously issued by
The Northeast Utilities System.



**Connecticut
Light & Power**

The Northeast Utilities System

www.cl-p.com



Information & Requirements *for* Electric Supply below 600 volts

2008 Edition

This publication
supersedes similar publications
previously issued by
The Northeast Utilities System.



**Connecticut
Light & Power**

The Northeast Utilities System

www.cl-p.com

***Prepared By The
2008 Revision Committee***

<i>David Benedetto</i>	<i>Meter Operations Berlin</i>
<i>David Coelho</i>	<i>Meter and Service Newtown</i>
<i>Henry Cosker</i>	<i>Meter Operations Berlin</i>
<i>Don Holmes</i>	<i>New Service Hartford</i>
<i>Howard Winslow</i>	<i>Standards Berlin</i>
<i>Jack Nims</i>	<i>Asset Management Wethersfield</i>

*The employees of the CT Light & Power
Company want to remind you to
WORK SAFELY!*

TABLE OF CONTENTS

Company Offices	viii
Definitions	xv
Introduction	xviii

SECTION 1: General

A. Safety — The First Priority	1
B. Service Request	2
C. Approvals	3
D. Temporary Service	3
E. Our Equipment on Private Property	3
F. Safe Access to Installation	3
G. Service Changes	5
H. Changes to Building Structure Effecting Service Entrance Equipment	5
I. Work Performed by Homeowners	5
J. Inspections	6
K. Employee's Identification	6
L. Theft of Service	6
M. Buildings Vacant for Greater Than Six Months	7
N. Services Disconnected Due to Flood, Fire, etc.	7

SECTION 2: Residential Cut & Reconnect Policy

SECTION 3: Types of Electric Service

A. Request for Electric Service	1
B. Line Extension	1
C. Primary Service	1
D. Types of Secondary Service	1

SECTION 4: Character of Supply (480 Volts and Below)

A. Supply Characteristics	1
B. Unusual Conditions	3
C. Two-Phase Supply	3
D. Three-Phase, 3-Wire, Delta Supply	3

SECTION 5: Our Service Facilities

A. General	1
B. Service Location	1
C. Number of Services	1
D. Disconnecting a Service at Your Request	2
E. Relocation of Service at Your Request	2

F. Removal of Electric Service at Your Request	2
--	---

SECTION 6: Your Service Facilities

A. Service Location	1
B. Service Equipment	1
C. Service Entrance Conductors	2
D. Pole-Mounted Service Equipment and Metering	3
E. Identification	3

SECTION 7: Third Party Communication Companies' Attachments to CL&P Distribution System Facilities

A. Scope	1
B. General	1
C. Protection Issues	2
D. Metering	3
E. Grounding	4
F. Pole Mounted Equipment	4

SECTION 8: Meter Installation

A. General	1
B. Standard Meter Installations	1
C. Meter Locations	2
D. Meter Equipment Mounting and Supports	4
E. Grounding	4
F. Cover Plates	5
G. Meter and Equipment Seals	5
H. Self-Contained Single-Phase Meter Installations	5
I. Self-Contained Three-Phase Meter Installations	7
J. Instrument (Current and Voltage) Transformer Installations	8
K. Telemetry	11
L. Platinum Service Options	13

SECTION 9: Your Utilization Equipment

A. General	1
B. Motor Installations	1
C. Motor Starting Current	2
D. Motor Protective Devices	2
E. Power Factor	3
F. System Disturbances	3

SECTION 10: Your Alternate Electric Energy Sources

A.	Non-Interconnected Generation (Standby or Emergency)	1
B.	Interconnected Generation	1
C.	Uninterruptible Power Supply (UPS)	2

SECTION 11: Illustrations

Figure 1	Temporary Electric Service Conduit System	2
Figure 1	Notes	3
Figure 2	Conduit Service: House End	4
Figure 3	Conduit Service: Supply End	5
Figure 4	Temporary Service from Overhead System	6
Figure 4	Notes	7
Figure 5	Overhead Service	8
Figure 6	Overhead Service Entrance Facilities	9
Figure 7	Service Mast	10
Figure 8	Special Service Attachment	11
Figure 9	Trenching Requirements	12
Figure 10	Self-Contained Meter Socket Sequence and Mounting Arrangement	13
Figure 11	Sequence of Meter and Service Equipment for Three-Phase Self-Contained 480Y/277v service and 280Y/120v Network Service	14
Figure 12	Sequence of Meter and Service Equipment for Three-Phase Self-Contained 480Y/277v service and 280Y/120v Network Service	15
Figure 13	Meter Installation-Private Property Pole - Your Conductors Overhead	16
Figure 14	Meter Installation-Private Property Pole - Your Conductors Underground	17
Figure 15	Permanent Pedestal Service – Site Built	18
Figure 16	Manufactured Pedestal Service	19
Figure 17	Single Phase: Self-Contained Metering Connections	20
Figure 18	Modular Meter Panels for Group Metering	21

	Single-Phase 120/240v or 120/208v	
	Three-Phase 208/120v Network	
	Three-Phase 480/277v	
Figure 19	Single-Phase: Self-Contained Metering to Multiple Mobile Homes	22
Figure 20	Self-Contained Outdoor Meter Socket Installation	23
Figure 21:	Three-Phase: Self-Contained Metering Connections	24
Figure 22	Outdoor Instrument Transformer Meter Socket with Test Switch	25
Figure 23	Instrument Transformer Connections	26
Figure 24	Combination Main Switch and Instrument Transformer Enclosure	27
Figure 25	Instrument Transformer Installation	28
Figure 25	Notes	29
Figure 26	Telephone AMR Equipment Diagram	30
Figure 27	Meter Interface Enclosure	31
Figure 28	Cell Site Metering Pedestal	32
Figure 29	Typical Remote Communications Power Site	33
Figure 30	Typical Transfer Switch Installation in Conjunction with your Auxiliary Supply	34
Figure 31	Cold Sequence Metering	35
Figure 32	Hot Sequence Metering	36

SECTION 12: Approved Meter Equipment Requirements

General Requirements	3-4
Commercial Requirements	5
Single-Phase Residential/Commercial 100 Amp - 200 Amp	6-8
Meter Pedestals Single-Phase Residential/Commercial 200 Amp	9
Single-Phase Residential/Commercial 320 Amp	9-10
Three-Phase Commercial 200 Amp - 320 Amp	11-13
Group Metering Single-Phase Residential/Commercial	14
Group Metering Three-Phase	15

208Y/120 Group Metering Three-Phase 480Y/277	16
Combination Circuit Breaker and Instrument Transformer Enclosure 120/240 Volt and 208Y/120 Volt Bar Type	17
Combination Circuit Breaker and Instrument Transformer Enclosure 480Y/277 Volt Bar Type	18
Combination Circuit Breaker and Instrument Transformer Enclosure 480Y/277 Volt Window Type)	19
Combination Fused Entrance Switch and Instrument Transformer Enclosure 120/240 Volt and 208Y/120 Volt Bar Type	20
Combination Fused Entrance Switch and Instrument Transformer Enclosure 480Y/277 Volt Bar Type	21
SECTION 13: Index	
Index	1
Project Checklist for New Services	6
Project Checklist for Service Updates	7
Checklist for Instrument Transformer Rated Installations	8

COMPANY OFFICES

Cheshire Office

705 West Johnson Avenue
Cheshire, CT 06410

Hartford Office

410 Sheldon Street
Hartford, CT 06106

Madison Office

135 New Road
Madison, CT 06443

Middletown Office

49 Randolph Road
Middletown, CT 06457

New Milford Office

41 Park Lane Road
New Milford, CT 06776

Newtown Office

20 Barnabas Road
Newtown, CT 06470

Norwalk Office

Tindall Avenue
Norwalk, CT 06851

Simsbury Office

34 Hopmeadow Street
Weatogue, CT 06089

Stamford Office

626 Glenbrook Road
Stamford, CT 06906

Tolland Office

48 Tolland Stage Road
Tolland, CT 06084

Torrington Office

174 Franklin Street
Torrington, CT 06790

Waterbury Office

250 Freight Street
Waterbury, CT 06722

Waterford Office

Myrock Avenue
Waterford, CT 06385

Willimantic Office

1270 Main Street
Willimantic, CT 06776

TO CONTACT US:

**Call Toll-Free: 1-800-286-2000 or
From Hartford Exchange call: 947-2000**

**Ask for “New Service Job Designer” in the appropriate CL&P
office.**

**A directory of Job Designers, sorted by town assignment, is
provided for registered contractors at our website:
www.cl-p.com**

**To electronically submit a CL&P “Service Request”,
contact us at our website address:
www.cl-p.com**

**To call in a “Service Request ” or
to call the CL&P Clearing Desk,
call toll-free: 1-888-544-4826**

**“CALL BEFORE YOU DIG”
CONNECTICUT
1-800-922-4455**

Town	CL&P Office	Town	CL&P Office
Abington	Willimantic	Colchester	Middletown
Addison	Middletown	Colebrook	Torrington
Almyville	Willimantic	Collinsville	Simsbury
Amston	Middletown	Columbia	Willimantic
Andover	Willimantic	Cornwall	Torrington
Ashford	Tolland	Cornwall Bridge	Torrington
Attawaugan	Willimantic	Cos Cob	Greenwich
Atwoodville	Willimantic	Coventry	Willimantic
Avon	Simsbury	Cromwell	Middletown
Baileyville	Middletown	Crystal Lake	Middletown
Baltic	Willimantic	Danbury	Newtown
Bantam	Torrington	Danielson	Willimantic
Barkhamsted	Torrington	Darien	Stamford
Bashan	Middletown	Dayville	Willimantic
Beacon Falls	Torrington	Deep River	Madison
Berlin	Cheshire	Dobsonville	Tolland
Bethany	Waterbury	Durham	Middletown
Bethel	Newtown	Eagleville	Willimantic
Bethlehem	Torrington	East Berlin	Cheshire
Black Hall	New London	East Canaan	Torrington
Bloomfield	Simsbury	East Granby	Simsbury
Bolton	Hartford	East Haddam	Middletown
Branford	Madison	East Hampton	Middletown
Bridgewater	Newtown	East Hartford	Hartford
Bristol	Cheshire	East Hartland	Simsbury
Broad Brook	Tolland	East Lyme	New London
Brookfield	Newtown	East Windsor	Tolland
Brooklyn	Willimantic	Eastford	Willimantic
Buckingham	Middletown	Ekonk	Willimantic
Burlington	Torrington	Ellington	Tolland
Canaan	Torrington	Elmville	Willimantic
Canterbury	Willimantic	Elmwood	Simsbury
Canton	Simsbury	Enfield	Tolland
Centerbrook	Madison	Essex	Madison
Central Village	Willimantic	Fabyan	Willimantic
Chaplin	Willimantic	Falls Village	Torrington
Cheshire	Cheshire	Farmington	Simsbury
Chester	Madison	Fenwick	Madison
Clarks Corner	Willimantic	Forestville	Cheshire
Clinton	Madison	Franklin	Willimantic
Cobalt	Middletown	Gales Ferry	New London
Gaylordsville	New Milford	Liberty Hill	Willimantic

Town	CL&P Office	Town	CL&P Office
Georgetown	Newtown	Lime Rock	Torrington
Gildersleeve	Middletown	Lisbon	Willimantic
Gilead	Middletown	Litchfield	Torrington
Glasgo	Willimantic	Little Haddam	Middletown
Glastonbury	Middletown	Lyme	New London
Goshen	Torrington	Madison	Madison
Granby	Simsbury	Manchester	Hartford
Greenwich	Greenwich	Mansfield	Willimantic
Griswold	Willimantic	Mansfield Center	Willimantic
Grosvenordale	Willimantic	Marble Dale	New Milford
Groton	New London	Marion	Cheshire
Grove Beach	Madison	Marlborough	Middletown
Guilford	Madison	Mechanicsville	Willimantic
Gurleyville	Willimantic	Melrose	Tolland
Haddam	Middletown	Meriden	Cheshire
Haddam Neck	Middletown	Merrow	Willimantic
Hadlyme	New London	Middle Haddam	Middletown
Hallville	New London	Middlebury	Waterbury
Hamburg	New London	Middlefield	Middletown
Hampton	Willimantic	Middletown	Middletown
Hanover	Willimantic	Milldale	Cheshire
Hartford	Hartford	Millington	Middletown
Hartland	Torrington	Monroe	Newtown
Harwinton	Torrington	Montville	New London
Hazardville	Tolland	Moodus	Middletown
Hebron	Middletown	Moosup	Willimantic
Higganum	Middletown	Morris	Torrington
Hop River	Willimantic	Mystic	New London
Hydeville	Tolland	Naugatuck	Waterbury
Indian Neck	Madison	New Britain	Cheshire
Ivorytown	Madison	New Canaan	Norwalk
Kensington	Cheshire	New Fairfield	Newtown
Kent	New Milford	New Hartford	Torrington
Killingly	Willimantic	New London	New London
Killingworth	Madison	New Milford	New Milford
Knollwood	Madison	New Preston	New Milford
Lakeside	Torrington	Newfield	Middletown
Lakeville	Torrington	Newington	Cheshire
Lebanon	Willimantic	Newtown	Newtown
Ledyard	New London	Niantic	New London
Leetes Island	Madison	Noank	New London
Town	CL&P Office	Town	CL&P Office
Norfolk	Torrington	Redding	Norwalk

Town	CL&P Office	Town	CL&P Office
North Canaan	Torrington	Redding Ridge	Norwalk
North Granby	Simsbury	Ridgefield	Newtown
North Plain	Madison	Riverside	Greenwich
North Stonington	New London	Riverton	Torrington
North Thompsonville	Tolland	Rockfall	Middletown
Northfield	Torrington	Rockland	Madison
Norwalk	Norwalk	Rockville	Tolland
Nut Plains	Madison	Rocky Hill	Hartford
Oakdale	New London	Rogers	Willimantic
Oakville	Waterbury	Rowayton	Norwalk
Old Lyme	New London	Roxbury	Newtown
Old Mystic	New London	Sadds Mills	Tolland
Old Saybrook	Madison	Salem	New London
Oneco	Willimantic	Salisbury	Torrington
Orcuttville	Tolland	Saybrook Point	Madison
Oxford	Waterbury	Scantic	Tolland
Pachaug	Willimantic	Scotland	Willimantic
Pawcatuck	New London	Seymour	Waterbury
Pequabuck	Cheshire	Sharon	Torrington
Phoenixville	Willimantic	Sherman	New Milford
Pine Meadow	Torrington	Short Beach	Madison
Pine Orchard	Madison	Simsbury	Simsbury
Plainfield	Willimantic	Somers	Tolland
Plainville	Cheshire	Somersville	Tolland
Plantsville	Cheshire	Sound View	New London
Pleasant Valley	Torrington	South Glastonbury	Middletown
Plymouth	Torrington	South Kent	New Milford
Plymouth	Cheshire	South Lyme	New London
Pomfret	Willimantic	South Windsor	Tolland
Pond Meadow	Madison	Southbury	Waterbury
Ponset	Middletown	Southington	Cheshire
Poquetanuck	New London	Sprague	Willimantic
Portland	Middletown	Spring Hill	Willimantic
Preston	New London	Stafford	Tolland
Prospect	Waterbury	Stafford Springs	Tolland
Putnam	Willimantic	Staffordville	Tolland
Putnam Heights	Willimantic	Stamford	Stamford
Quaddick	Willimantic	Sterling	Willimantic
Quaker Hill	New London	Sterling Hill	Willimantic
Quinebaug	Willimantic	Stonington	New London
Town	CL&P Office	Town	CL&P Office
Storrs	Willimantic	West Granby	Simsbury
Suffield	Tolland	West Hartford	Simsbury

Town	CL&P Office	Town	CL&P Office
Taconnic	Torrington	West Hartland	Torrington
Talcottville	Tolland	West Mystic	New London
Tariffville	Simsbury	West Redding	Norwalk
Terryville	Cheshire	West Simsbury	Simsbury
Thomaston	Torrington	Westbrook	Madison
Thompson	Willimantic	Westchester	Middletown
Tolland	Tolland	Westfield	Middletown
Torrington	Torrington	Westminster	Willimantic
Tylerville	Middletown	Weston	Norwalk
Uncasville	New London	Westport	Norwalk
Union	Tolland	Wethersfield	Hartford
Union City	Waterbury	Willimantic	Willimantic
Unionville	Simsbury	Willington	Tolland
Vernon	Tolland	Wilsonville	Willimantic
Versailles	Willimantic	Wilton	Norwalk
Voluntown	Willimantic	Winchester	Torrington
Warehouse Point	Tolland	Windemere	Tolland
Warren	New Milford	Windham	Willimantic
Warrenville	Tolland	Windsor	Hartford
Washington	New Milford	Windsor Locks	Tolland
Washington Depot	New Milford	Windsorville	Tolland
Waterbury	Waterbury	Winsted	Torrington
Waterford	New London	Winthrop	Madison
Watertown	Waterbury	Wolcott	Waterbury
Wauregan	Willimantic	Woodbridge	Waterbury
Weatogue	Simsbury	Woodbury	Waterbury
Wequetequock	New London	Woodstock	Willimantic
West Ashford	Tolland	Woodstock Valley	Willimantic
West Cornwall	Torrington		

DEFINITIONS

For additional definitions, refer to Section 100 of the National Electrical Code.

AMR: Automatic Meter Reading.

Approved Equipment: Published list of metering equipment approved for use by CL&P.

Clearing Desk: The CL&P Service Request Clearing Desk is another way for our customers and contractors to communicate their electric service needs to us. 1-888-544-4826

Code: The State of Connecticut-approved version of the National Electrical Code and/or applicable state or local codes and ordinances.

Conduit System: Our electrical distribution facilities installed underground, in electrical grade Schedule 40 PVC conduit.

Instrument Transformer Installations : A service requiring potential transformers and/or current transformers.

Labeled: Equipment or material to which a label, symbol, or other identifying mark of an organization has been attached and that is acceptable to the authority having jurisdiction and concerned with product evaluation, that maintains periodic inspection of production of labeled equipment or materials, and by whose labeling the manufacturer indicates compliance with appropriate standards or performance in a specified manner.

Listed: Equipment, materials, or services included in a list published by an organization and concerned with evaluation or products or services, that maintains periodic inspection of production of listed equipment or materials or periodic evaluation of services, and whose listing states that either the equipment, material, or services meets identified standards or has been tested and found suitable for a specified purpose.

Metering Sequence:

Cold Sequence: Main disconnect required before the self-contained meter or instrument transformers.

Hot Sequence: No main disconnect before meter.

Network System: A distribution system in which the secondaries of the distribution transformers are connected to common conductors for supplying power directly to a customer's service. These are special systems generally located in downtown areas of cities.

Primary/High Voltage Service: Above 600 volts (this booklet does not apply).

Self-Contained: A meter capable of measuring the entire amperage of the electric service without the use of current and/or voltage transformers.

Service: The conductors and equipment for delivery of electric energy from our distribution (supply system) to the wiring system of the premises served.

Secondary Service: 600 volts or less (the rules of this booklet apply).

Service Drop: Our overhead service conductors between our facilities and your structure.

Service Entrance Capacity: This is the rating of the service equipment in amperes.

Service Equipment: The necessary equipment, usually consisting of the main control, circuit breaker or fuses and their accessories, and intended to constitute the main control and means of cutoff of the supply.

Service Lateral: The underground service conductors and conduit starting at the street main, at the top of a riser on a pole, from a transformer or other structure, and connecting to the service point.

Service Location: The approved point of attachment of our service drop or their approved point of entry of our service lateral to building.

Service Point: The point of connection between the facilities of the service utility and the premises wiring.

Slip Meter Riser: (Slip Joint) for use in electrical conduit system service entrance applications with incoming service conduit diameters ranging from 3" to 4".Complies with NEC 300-5 which requires protection for buried cables in areas subject to frost heave, ground settlement, etc.

Spoils: The soil removed from an excavation.

Suitable Backfill: Soil that does not contain ashes, cinders, shells, frozen material, loose debris or stones larger than 2" in maximum dimension.

Underground Manhole System: Our electrical distribution facilities installed in the ground in manholes, vault, duct banks, pads, etc.

Us-We-Our: The Connecticut Light and Power Company.

You-Your: The person or entity responsible for paying our bill or their agents who are responsible for work being done.

INTRODUCTION

This booklet is published for the benefit of our customers, architects, engineers and contractors to provide a convenient reference. However, design or construction should not be undertaken until complete information is obtained from us. Such information and assistance is available from our New Service, Account Executive, Meters and Service, or Clearing Desk Departments. See page viii for location of our offices.

We supply electricity subject to our Rules and Regulations listed in this booklet and Terms and Conditions, policies and procedures, rate schedules, and industry standards—all of which are made a part of these requirements. These requirements are not included in this booklet but are available upon request.

Legal restrictions, changes in the art, judgment and safety require this booklet to be revised from time to time and we reserve the right to make such revisions. Our present schedule calls for publishing any such revisions in 2010.

We endeavor to supply electricity adequately and reliably. We do not guarantee a continuous supply and do not assume liability for direct or consequential loss or damage to persons or property due to the supply delivered, or as a result of any interruption or variation in the supply. Momentary interruptions can occur due to the normal operation of our system's protective devices.

Failure to comply with our requirements, applicable codes, or orders of an enforcement authority can result in our refusal to energize the service or in the disconnection of an existing service.

The Connecticut Light and Power Company would like to acknowledge the Electrical Contractors Associations, State of Connecticut Officials and Town Officials (especially Electrical Inspectors) for their efforts and cooperation with CL&P and among themselves to provide the customers in the State of Connecticut with safe and reliable power. We wish to thank you for your assistance and look forward to working with all of you in the future to ensure the safety of our customers and workers.

ELECTRICAL CONTRACTORS

Your “Service Requests” are only a >CLICK< away!

Quick and Easy * Self Serve * Convenient and Secure

Electrical Contractors are in control with CL&P's online Request for Electric Service system. Contractors can initiate, submit and monitor the status of a particular request for CL&P electric service, anytime, at www.cl-p.com.

Each electric service request is assigned a unique identification number allowing you to monitor the progress of each service requests. You can:

- View CL&P's planned scheduled date.
- View the status on job requirements such as municipal inspection approvals and easements.
- Identify the CL&P Job Designer assigned to the request.
- Access all of your requests for electric service 24/7.

Registering is free and easy.

1. Visit “For My Business” on www.cl-p.com.
2. Click on Service Request for Contractors
3. Follow instruction on “How to Register”.

Request for Electric

www.cl-p.com

For assistance or more information, call CL&P's New Service Clearing Desk at 1-888-LIGHTCO (1-888-544-4826) or email us at:

CL&PSVC@NU.com

SECTION 1: General

A. Safety - The First Priority

1. Any contact with our wires may cause serious injury or death. Treat all downed, hanging or burning wires as though they are "LIVE" - energized - and stay away from them. Do not regard the covering which may be observed on our wires as insulation.
2. Report any downed, hanging or burning wires to CL&P at 1-800-286-2000 or the police or fire department. In the Hartford area you must dial 947-2000.
3. Connecticut State law requires contacting "Call Before You Dig" two (2) full working days prior to doing any excavation, digging holes, or driving posts regardless of whether it is within the street or on private property. Obtain information by calling 1-800-922-4455.
4. Equipment such as ladders, scaffolding, etc., regardless of what they are made of, can become electrified if brought in contact with wires. Use extra caution when installing siding, painting, cleaning gutters or other reasons to work near our facilities.
5. Removal or relocation of existing CL&P overhead or underground service equipment is prohibited. Contact CL&P if removal or relocation is necessary.
6. **Do not enter or open existing electrical structures such as handholes, transformer pads or switch vaults.** Call CL&P at 1-800-286-2000 or 947-2000 in Hartford and ask for the Electric Service Designer in the project area.
7. Equipment such as cranes, backhoes, etc., shall never be operated within 10 ft. of our overhead distribution conductors. Refer to OSHA limit of approach regulations.
8. Swimming pools and spas must not be installed beneath our overhead facilities or above our underground facilities.

9. Where hazards exist, ground fault circuit interrupters must be used in accordance with code. In addition, we strongly recommend their installation on existing wiring.
10. Never replace/install fuses or breakers, for main switch or branch circuits, with other than the proper size for the installation.
11. Proper installation of generators or other power sources is essential to avoid electrical source feeding back into our lines and endangering unsuspecting utility workers. See Section 10.A and Section 11, Figure 30 (Page 34).
12. Antennas, banners, flags, customer lighting, signs or similar customer equipment shall not be attached to our poles.

B. Service Request

1. Our Service Request procedure is meant to do the following:
 - a. Provide methods for responding to and processing your electric service request.
 - b. Encourage you to contact us far enough in advance to allow for proper planning by both you and us.
 - c. Provide you with information which will:
 - Designate the service location.
 - Specify the type and character of supply that is available.
 - Specify the location and requirements for our metering equipment.
 - Provide the available fault current for your specific installation.
 - Advise you of advance charges, if any.
 - Advise you of any special requirements.
 - Advise you of an estimated completion date.
2. A CL&P Service Request must be submitted for any new, changed, removed or temporary service. A Service Request can be submitted via phone (1-888-544-4826) or Internet (www.cl-p.com). The request should be submitted at the

earliest possible date and filled out completely, including load data. You are responsible for making service requests to others: i.e., telephone, cable TV, gas, water and for coordinating their activities.

C. Approvals

We will not energize a service until it is approved by the local inspecting authority and it meets the requirements outlined in this book.

D. Temporary Service

1. We will supply temporary service when it can be served from our existing lines or facilities. You must:
 - a. Supply and maintain suitable service entrance equipment (weatherproof, if required).
 - b. Pay, in advance, the cost of connecting and disconnecting this service. This includes the cost of installation and removal of any poles, wires, transformers, meter equipment, or other facilities. These charges are in addition to the regular rate applicable to the use of energy.
2. Requirements for temporary service are shown in Section 11, Figure 1 (pages 2 & 3) and Figure 4 (pages 6 & 7).


E. Our Equipment on Private Property

All our equipment located on your premises, such as poles, conductors, meters, current transformers, auxiliary metering equipment, transformers, ducts, etc., shall remain our property and may be removed by us in the event such equipment is no longer needed.

F. Safe Access to Installation

We require the right (at all reasonable times) to enter your premises to erect, remove, operate or maintain our facilities and to read and test our meters. The access area must be clear of obstacles and capable of carrying heavy vehicles and equipment if they are required. We are not responsible for restoring trees, shrubs and/or grass if we cause damage because of inadequate access.

Warning and Clearance Diagram



G. Service Changes

When changes or alterations are made to your service equipment, the service entrance and meter installations must conform to both our **current** requirements and applicable Codes.

For multiple unit residential buildings, all common facilities (hallway lighting, alarm systems, well pumps, etc.) must be connected to an owner's meter.

H. Changes to Building Structure Affecting Service Entrance Equipment

When changes, alterations or additions to an existing structure affect the attachment of service entrance equipment, the attachment point and installation must conform to both our **current** requirements and applicable Codes.

I. Work Performed by Homeowners

Homeowners are allowed by CT State law to perform electrical work on their single family, owner-occupied residence. All of the work must be performed by the homeowner personally and all required permits must be obtained. Homeowners are not allowed to cut and reconnect their service or remove the CL&P meter. Homeowner work must be inspected and approved by the local municipal code-enforcement official.

The homeowner has two options to complete this work:

1. The homeowner builds a parallel service; service entrance, weatherhead and conduit, meter box, main breaker, etc. This service can be backfed on the customer's side of the main switch to the existing service until a municipal inspection approval is issued. At that time we will cut and reconnect the new service equipment at the weatherhead.
2. The homeowner can coordinate with us to cut the service, perform the service upgrade, obtain a municipal inspection approval and call us back to reconnect the service.

Under both options the homeowner must take out a municipal permit and a Service Request. Contact us in advance to review the planned work, i.e., service location change, upgrade, etc. and coordinate the cut and reconnect. The upgraded service shall not be energized until a municipal approval is given. It is the responsibility of the homeowner to schedule an appointment with us and the municipal code-enforcement official.

Important:

If work is going to be performed by a homeowner (under a permit taken out by the homeowner) a licensed electrician is not allowed to perform the cut and reconnect. If a licensed electrician is going to perform the cut and reconnect they must abide by the State-approved Cut and Reconnect policy and take out the permit under their license.

J. Inspections

Our inspection of your service facilities or wiring is not an approval of conformance to applicable codes. The purpose of our inspection is to ensure that our requirements are met with respect to line, load, and ground connections, the meter installations, and that the installation is in conformance with this booklet.

K. Employee Identification

All Company employees carry photo identification which they will present on request.

L. Theft of Electric Service

Connecticut General Statutes C.G.S. Section 53a-127(c) prohibits theft of electric service.

Theft of electrical service is defined as the taking, or acceptance, of electric service without the knowledge or consent of the Company. This includes any method or device used by any person(s) which prevents an electric meter from accurately registering the quantity of electricity supplied by the Company. Theft of electric service is unlawful, unsafe and can result in serious injuries, fires, explosions and death!

Where there is evidence of meter tampering and/or the diversion of electric service, such person or persons responsible shall be liable for criminal prosecution under the penalty of all applicable laws. All lost revenue, intended or unintended, is subject to recovery by the Company.

To report suspected meter tampering, or diversion of electrical service, please report it to CL&P's confidential (no need to identify yourself) energy theft hotline at 1-800-286-5350.

M. Buildings Vacant for Periods Greater Than Six Months

State of CT House Bill 6292: If an owner of a building or portion of a building that has been unoccupied and disconnected from the electric distribution system for a period of six months or longer wishes to resume delivery of electricity to such building or portion of such building, the owner shall contract with an electrician licensed pursuant to chapter 393 of the general statutes, at the expense of the owner of such building, to inspect the electric conductors and equipment up to and including the main device to disconnect electric power to such building. The electrician shall provide written notice to the electric distribution company, as defined in section 16-1 of the general statutes, authorized to provide electric distribution services to the service area in which such building is located that such equipment is electrically safe and does not constitute a public safety hazard. Upon receipt of the written notice, the electric distribution company shall promptly resume delivery of electricity to such building or portion of such building.

Contact CL&P at 1-800-286-2000 or 860-947-2000 in the Hartford area to provide notice in compliance with this law.

N. Services Disconnected Due to Flood, Fire or Similar Circumstance

If a service has been disconnected due to damage caused by flood, fire or similar circumstance it will not be reconnected without notification by an appropriate public official such as the Fire Marshall or Code Enforcement Official.

*The employees of the CT Light & Power
Company want to remind you to
WORK SAFELY!*

SECTION 2: Residential Cut & Reconnect Policy

Residential Cut and Reconnect Policy Restricted to Two-Wire 120 Volt, Three-Wire 120/240 Volt or Three-Wire 120/208 Volt Single-Phase Overhead Residential Services of 400 Amps or Less.

Definitions

Licensed Electrician - a Master electrician holding a valid E-1 or E-9 license issued by the State of Connecticut. Department of Consumer Protection - Occupational & Professional Licensing Division. The Licensed Electrician (hereinafter referred to as the electrician) is responsible for all work performed under this policy.

E-2 License - an E-2 license holder can only perform electrical work while under the employ of a contractor licensed for such work.

E-9 License - an E-9 license-holder is restricted to residential and light commercial work only. New E-9 licenses are no longer offered in Connecticut.

Local Municipal Authority - a duly appointed building code official, responsible for inspecting and ensuring that contractor work is in compliance with all applicable local, State and Federal regulations.

Self-Contained Meter - a meter capable of measuring the entire amperage of the electric service without the use of current and/or voltage transformers.

Policy

1. In order to perform a cut and reconnect a Licensed E-1 or E-9 Electrician must read the policy and acknowledge understanding and compliance by signing a letter of agreement and returning it to CL&P. Only Electricians who have signed a letter of agreement will be allowed to cut and reconnect under this policy. **Homeowners are not authorized to cut and reconnect electric services.** See Section 1, Part I, page 5, for homeowner service changes.

2. The electrician shall cut the service entrance cable at the weatherhead, replace or repair the service and re-connect it in compliance the requirements of this booklet. This work may also be performed by an E-2 Journeyman or Apprentice working under the direct supervision of an E-1 or E-9 licensee. All applicable rules of the State of Connecticut Department of Consumer Protection - Occupational & Professional Licensing Division apply.
3. The electrician must contact us at least fifteen days prior to starting work to avoid potential code violations or non-compliance with our requirements.
4. The electrician must obtain a valid Service Request number, either through the internet on the CL&P website (cl-p.com) or by telephone (1-888-544-4826). The request must indicate in the job description that the work involves “**cut and reconnect**”. Further, this work must be completed within 60 days from the date of the request.
5. The electrician must receive our approval **prior** to starting work if the point of attachment is going to be changed or there are existing clearance conflicts.
6. The electrician is responsible for obtaining the appropriate permits from the local municipal authority in advance of starting work. Jumpers and optically clear meter socket covers are available at most municipal building official offices or the local CL&P office.
7. The service must be cut at the point of attachment on the line side of the existing service drop connectors.
8. The service must be reconnected utilizing properly sized connectors as listed below.
 - Phase/Hot Leg /Conductor
 - Properly taped Parallel Groove Connector
 - Properly taped Pliers-applied Wedge Connector
 - Insulated Compression Sleeve
 - Neutral Conductor
 - Bare Parallel Groove Connector
 - Bare Pliers-applied Wedge Connector
 - Bare Compression Sleeve

9. The electrician will install only Company-approved jumpers to avoid damage to the meter socket and optically clear meter socket cover(s) to ensure public safety and provide access for visual inspection.
10. The electrician is responsible for returning the old meter to the Company by leaving it near the new meter socket. **In no case shall the old meter be reinstalled in the new meter socket.**
11. All CL&P requirements, the National Electric Code, State and Municipal building requirements must be met.
12. The electrician is responsible for obtaining municipal approval and must advise the Company (1-888-544-4826) within one business day of completion of Steps 2 through 10, above.

The Company

1. The Company will install a meter after ten business days unless notified of a building code violation by the Local Municipal Authority. **Installation of a meter does not supersede the requirements of an inspection approval by the Local Municipal Authority.**

Non-Compliance and Violations

1. In cases of non-compliance with any of the requirements of the Cut & Reconnect Policy, including non-compliance with NEC, OSHA, and State and local Building codes, the Company will send a written inquiry to the electrician, customer and Local Municipal Authority, as necessary to resolve the problem.
2. Multiple letters to an electrician will result in notification of the appropriate State and Municipal authorities. Such notification constitutes a violation letter.
3. The electrician will be notified in writing that a violation letter has been sent and that their privilege to perform work under the Cut & Reconnect Policy may be suspended. In the case where risk of public safety is a factor, the Company will **immediately** suspend Cut & Reconnect privileges for said electrician.

4. The Occupational and Professional Licensing Division of the State of Connecticut Department of Consumer Protection will review violations to determine if Connecticut General Statute, Section 20-334 has been violated and will take appropriate action, up to and including penalties, as described in the Connecticut General Statute, Section 20-341.
5. The electrician will be billed for any and all costs that may be incurred to correct a violation.

SECTION 3: Types of Electric Service

A. Electric Service Request

When we receive the Electric Service Request we will determine the type of service, based on your location and the size and character of the proposed load.

B. Line Extensions

You should consult with us at a very early date about any situation that will require a single or three-phase line extension along a town road, state highway, or into new residential developments, commercial complexes, or industrial parks. Under certain circumstances, customer charges will apply. In addition, we have special policies for line extensions into new residential developments.

C. Primary/High Voltage Service

Requirements for primary/high voltage service (over 600 volts) are not included in this booklet. To provide such service, we need early and detailed consultation with you.

D. Types of Secondary Service

Refer to Section 4: Characteristics of Supply.

1. Overhead service from overhead system.

- a.** We will attach our service drop to the structure at the approved location which is accessible to our line mechanic and high enough to provide adequate clearance. See Section 11, Figures 5, 6 and 7. The minimum clearances are:
 - **Twelve feet** above finished grade, sidewalks, residential driveways and commercial areas not subject to truck traffic and located more than 25 feet in any direction from a swimming pool, swimming area, or diving platform.

- **Sixteen feet** over roads, streets, alleys, parking lots or other areas subject to truck traffic.
- b. Your service entrance conductors or cable shall be terminated with an approved detachable weatherhead and be safely accessible from a ladder on the ground. See Section 11, Figure 5.
- c. The location of your weatherhead shall be positioned to permit the installation of our service drop at or below the weatherhead. A minimum of 20 inches of conductor must extend from the weatherhead to make a connection to the service drop with a proper drip loop. See Section 11, Figure 6.
- d. You are responsible for providing adequate tree trimming and/or tree removals for your service.

2. Service Lateral from Overhead System or from Conduit System

Note: Consult a New Service Job Designer or Account Executive for a conduit service 200 feet or longer.

You will be responsible for the following:

- a. Providing a trench with conduit at a depth that will provide a cover of 24 inches above the conduit and which will run from our designated service location at the foundation to our facilities. **The designated service location shall be in direct line of sight to CL&P's distribution facilities. You must consult with the Company for any installations that may not conform to this requirement. See Section 8, Item C.1 (page 2) for additional details.** The conduit shall be electrical grade Schedule 40 PVC (minimum of 3 inch diameter.) Provide and install caution tape in the trench backfill even if the conduit is encased in concrete. **Note: Metallic foil tape is NOT acceptable.** See Section 11, Figure 9, note E (page 12)
- b. Coordinating with other utilities such as telephone, cable TV, water and gas.

- c. Providing and installing conduit, including an approved slip joint, from the metering equipment to the trench conduit. The line side conduit shall enter the meter cabinet through the bottom left knock-out. The slip joint shall be securely fastened to the building with one clamp. See Section 11, Figure 2 (page 4). Contact us for conduit size (minimum of 3 inch diameter).
- d. At the service end, providing and installing an electrical grade Schedule 40 PVC sweep (or steel, if required by us) with a 90 degree bend, 24 inch minimum radius from the slip joint to the conduit in the trench.
- e. If the designated point on the distribution system is on the opposite side of the road, a conduit road crossing is preferable. Such road crossing is at the customer's expense. However, an overhead crossing, if allowed by the local municipality, may be installed at the customer's expense. This includes the pole, the length of customer-dedicated road crossing conductor and any required guying. If a road crossing pole exists or is provided by another utility, a customer's conduit service may be taken from that pole. Contact the New Service Job Designer whenever a road crossing is required.
- f. Providing and installing a galvanized steel sweep (or electrical grade Schedule 40 PVC if approved by us in advance) and conduit with cap at the riser pole if from our overhead system. The sweep shall be a 90 degree bend with a minimum 24 inch radius. See Section 11, Figure 3B, (page 5).
- g. Installing a 1/4 inch diameter nylon pulling line from the meter socket to the end of the conduit at our facilities (transformer pad, temporary dead-end, handhole or riser pole). Do not enter or open existing electrical structures such as handholes, transformer pads or switch vaults, when installing the pulling line. Call CL&P at 1-800-286-2000 or 947-2000 in Hartford and ask for the Electric Service Designer in the project area.

Note: *The end of the conduit at our facilities shall be capped and left accessible.*

- h. Providing and installing the ground assembly at the steel sweep at the customer's service entrance. The ground assembly shall consist of a ground clamp suitable for direct burial, No.6 bare copper wire, a ground rod connector and a five-eighth inch by eight foot ground rod. See Section 11, Figure 2, (page 4). We will install the grounding assembly on the steel sweep at the riser pole.
- i. Backfilling the trench before we install the cable. Exercise care to avoid damaging the conduit by not dropping rocks or frozen earth onto it.
- j. The trench shall be as straight as possible from the point of termination on the building to our facilities. **The total of all bends shall not exceed 225 degrees with no reverse bends.**
- k. Ensuring that proper clearances are maintained from travel ways, windows, doors, and any other structures per the following table.

Item	Minimum Distance (in feet)		
	In front of	To side of	Below
Door	20	10	-
Air Intake	10	10	25
Window	10	3	5
Fire Escape	20	20	-
Combustible Wall	6	6	-
Noncombustible Wall	5	3	-
Fuel Tanks (above & below grade)	10	10	-
Natural gas or propane connections	3	3	-
Gasoline dispensing unit	20	20	-

I. Installation and Maintenance Responsibilities for Conduit System Service Laterals:

- i) **Residential Service.** We will install our conductors in your conduit and terminate in your meter socket, main switch, trough, or other suitable device immediately

adjacent to the wall entrance. The Company will repair damaged service conduits once service conductors have been installed.

ii) **Commercial / Industrial Services to Service Entrance Capacity of 400 Amps Total or Less.** We will furnish the cable, install it in your conduit and terminate it at your meter socket, main switch, trough, duct box or other suitable device immediately adjacent to the wall entrance. We will maintain our cable. You will furnish, install and maintain the conduit and all conductors beyond the termination point. Refer to Section 8, Table A (page 18) for types of metering available.

iii) **Commercial / Industrial Services to Service Entrance Capacity of Over 400 Amps Total.** You will furnish, install, own and maintain all secondary conduit and conductors. You will loosely make up all transformer connections (CL&P supplied) to transformers to ensure proper conductor length, with the Company making the final connection. Transformer bushings should never be used as a stanchion in the course of pulling conductors.

3. Service Lateral from Underground Manhole System

Note: You must consult CL&P for this kind of service.

- a. Your service shall include approved conduit from the service entrance location to the property line or a point on the distribution system designated by the Company. You will furnish and install this conduit, including replacement, if necessary, for service upgrades. The Company will repair damaged service conduits once service conductors have been installed. The service entrance location must be immediately adjacent to the outside wall. **Contact the New Service Job Designer in advance for service changes in underground system areas.**
- b. We will install our conductors in your conduit. Charges will be in accordance with our policy. We will furnish, install and own the seal between your conduit and our conductors. We will maintain this seal at your request but will not be responsible for damage due to a leaking seal. You will furnish, install, own and maintain the seal between your conduit and the wall.

4. Temporary Service

See Section 1, Item D (page 3).

SECTION 4: Characteristics of Supply (480 Volts and below)

A. Supply Characteristics

1. We will supply and meter alternating current with a nominal frequency of 60 Hertz (cycles per second) and a nominal voltage as described in item 3 below.
2. If you desire a new service or an increase in capacity, you should contact us **before** purchasing any equipment or beginning any electric construction. We will designate the voltage and phase characteristics which will be available.
3. Normally, one of the following will be supplied:

Nominal Voltage	Phase	Wires	Comments
120/240	1	3	a,b,c,d
120/208	1	3	c,e
208Y/120	3	4	f,g,h
480Y/277	3	4	f,g,h

- a. In general, only single-phase service will be supplied to residential loads.
- b. Campgrounds and mobile home parks services must be 120/240 volts.
- c. ***The maximum single-phase service from an overhead distribution system is 400 amps, including the total rated capacity for multiple main switches. Under some circumstances, a 400 amp main disconnect may be required ahead of multiple sub-main switches whose total rated capacity exceeds 400 amps. Please consult with CL&P New Service Job Designer for all services over 400 amps.***

- d. ***Single-phase services over 400 amps and up to 1200 amps maximum must be fed from a padmount transformer. The largest single-phase service allowed is 1200 amps. Please consult with CL&P New Service Job Designer for all services over 1200 amps.***
 - e. Three-phase supply is not normally available for single family housing. For large residential complexes, which may require a three-phase service to the building, individual residential customers will be served only with single-phase 120/208v.
 - f. ***The maximum three-phase service allowed from an overhead distribution system is 400 amps, including the total rated capacity for multiple main switches. Under some circumstances, a 400 amp main disconnect may be required ahead of multiple sub-main switches whose total rated capacity exceeds 400 amps. Please consult with CL&P New Service Job Designer for all services over 400 amps.***
 - g. ***The largest standard three-phase underground service CL&P can provide with one transformer is 3000 amps. Please consult with CL&P New Service Job Designer for all services over 3000 amps.***
 - h. Three-phase service is normally available for supply loads of 75 kVA or larger only.
4. We cannot guarantee to maintain the voltage level of these nominal values under all conditions; however, voltage will normally be maintained within reasonable limits and as specified by the regulatory authority. We recommend the use of suitable voltage regulating devices where equipment sensitive to voltage is in use. See table in Section 4, item 3 (page 1).
5. The voltage rating of your equipment should be compatible with the normal voltage which we supply. See table in Section 4, item 3 (page 1).

B. Unusual Conditions

We may refuse to supply electric services to loads which have characteristics which might adversely affect the supply to other customers, such as harmonic distortion, voltage fluctuations, noise or low power factor.

C. Two-Phase Supply

We no longer offer new 2-phase supply. If your present service is 2-phase, consult us before making any changes or additions.

D. Three-Phase, 3-Wire, Delta Supply

We no longer offer new 3-phase, 3-wire, Delta supply. If you have this type of supply, consult us before making any changes or additions.

*The employees of the CT Light & Power
Company want to remind you to
WORK SAFELY!*

SECTION 5: Our Service Facilities

A. General

1. We or our agents shall install all facilities which we will own, operate and maintain. We or our agents shall perform all work on our poles and equipment except as noted in Section 6, Item D (page 3).
2. You may be required to contribute to the cost of installing service facilities. Where we assume responsibility for future operation and maintenance, we shall hold title of ownership to such facilities.
3. Service installations involving special conditions due to size of load, physical limitations, rate application, or other special requirements of the customer will be subject to joint study and agreement with us.
4. **All connecting and disconnecting of our facilities will be made by us or our agents.** However, in case of single-phase residential services, qualified electricians will be permitted to cut and reconnect such services in compliance with our Cut & Reconnect policy. See Section 2.

B. Service Location

We will designate the location for new, relocated or upgraded services. All services must meet the requirements of this booklet. It is your responsibility to request and obtain this information before you start work. A Service Request can be submitted via Internet (www.cl-p.com) or phone (1-888-544-4826).

C. Number of Services

1. Normally, only one service will be installed to a single building or structure.
2. Multiple services to one building or structure will not be permitted without the written approval of the local authority. These services shall not be interconnected.

3. Each service will be separately metered and will be billed as serving a separate customer under the appropriate rate.

D. Disconnecting a Service at Your Request

We will temporarily disconnect your service to allow you to perform maintenance, construction, or tree-trimming. We require a minimum of three working days notice to schedule the work. There may be a charge for this service if it is after normal working hours. Consult our local office for details.

E. Relocating a Service at Your Request

We will designate the service location for all relocated services. We require a minimum of five working days notice to schedule the work. There may be a charge for this service. Consult our local office for details.

F. Removal of Electric Service at Your Request

1. Building Demolition

We will remove all electrical services, meters and metering equipment, after receipt of your written request per State Law. All written requests shall be from the property owner. If the property to be demolished includes separately metered tenants the letter must be notarized. A form letter is available on our website. We will promptly confirm in writing (within 5 working days) to you that the services, meters and metering equipment have been removed.

2. Other than Demolition

If service and metering equipment must be removed from a building for a reason other than demolition, your written request is required. We require a minimum of five working days notice to schedule the work. Written confirmation will not be furnished unless it is requested.

SECTION 6: Your Service Facilities

A. Service Location

We will designate the location for a new service or change of service which shall be on the front or side of the building. The front of the building is considered to be the side adjacent to our distribution facilities. It is your responsibility to request and obtain this information **before** you start work. Refer to Section 1, Item B (pages 2 & 3).

B. Service Equipment

1. For Safety considerations, see Section 1, Item A, (pages 1 & 2).
2. The service equipment must be properly rated for voltage, current, interrupting duty, and fault current. Upon request, we will furnish the information necessary to select proper equipment. Higher than usual interrupting duty is required for main branch circuit protection devices when supplied from a network system or transformation capacity in excess of 100 kVA. Contact us for detailed requirements.
3. Service equipment shall be installed on the load side of the self-contained meters up to 240 volts.
4. **The following exceptions are installations where the main disconnect will be installed on the line side of the meter (cold sequence).**
 - a. **All 480 volt services.**
 - b. **Services fed from a CL&P network system. Contact us for detailed requirements, such as R type fuses, 100,000 amp fault current rating, and rejection clips. See Section 11, Figure 11 (page 14), Figure 16 (page 18) and Figure 18 (page 21).**
 - c. **Single phase, overhead, residential installations with multiple meter positions exceeding 400 Amps, as described in Section 4, Item A.3.c. You must consult with CL&P for these types of installations.**

5. Network service may require you to furnish a cable limiter cabinet. Consult with us in such instances.
6. There shall be no more than 6 disconnects per service grouped in any one location. See Section 11, Figure 19 (page 22), Figure 20 (page 23) and NEC Section 230-71(a).

Utilizing a main disconnect is the preferred installation to allow for additional meters beyond six. See Section 11, Figure 18 (page 21) and Figure 28 (page 32).

7. Fire Pumps - refer to NEC Article 695 for requirements. All fire pump and alarm circuits shall be metered. If the authority having jurisdiction requires that the fire pump or alarm service connections be ahead of the normal metering, then a separate service and meter shall be installed at the customer's expense. Consult with us in such instances. Refer to Section 8, Item J.2.c, page 10, for details.
8. For multiple unit residential buildings, all common facilities (hallway lighting, alarm systems, well pumps, etc.) must be metered separately per NEC, Section 210-25. This is commonly referred to as an owner's meter.

C. Service Entrance Conductors

1. Where a main switch or circuit breaker constitutes the service equipment for a residential single-phase installation, the minimum ampacity of the service entrance conductors and socket meter trough shall be at least equal to the rating of the main circuit breaker or the largest main fuse which can be installed in the service equipment.
2. For a single-phase installation to an individual customer where more than one switch or circuit breaker is permitted as the service equipment, the ampacity of the service entrance conductors and socket-meter trough shall be a minimum of 100 amperes but not less than code requirements.
3. For multiple-occupancy buildings, where up to six individual switches or circuit breakers function as the disconnecting means, the service entrance conductors must have adequate

ampacity for the load as determined by applying the methods and rules set forth in the code.

4. Metered and unmetered conductors **shall not** be contained in the same raceway or conduit.
5. Metered conductors from more than one meter shall not be contained in the same raceway or conduit.

D. Pole Mounted Service Equipment and Metering (Special Installation)

Service equipment and metering is permitted only on private property poles as shown in Section 11, Figures 13 and 14, (pages 16 and 17, respectively). ***With the exception of the pole and meter, all facilities beyond this service point will be furnished, installed, owned and maintained by you.*** Only one meter will be allowed on a private property pole. Consultation with us is required. You must sign our Application and License for Attachments form (OP5237). Service equipment and metering shall not be installed on street poles.

E. Identification

The contractor or electrician shall post their name, address, and telephone number at each installation to facilitate contacting the proper person.

ELECTRICAL CONTRACTORS

Your “Service Requests” are only a >CLICK< away!

Quick and Easy * Self Serve * Convenient and Secure

Electrical Contractors are in control with CL&P's online Request for Electric Service system. Contractors can initiate, submit and monitor the status of a particular request for CL&P electric service, anytime, at www.cl-p.com.

Each electric service request is assigned a unique identification number allowing you to monitor the progress of each service requests. You can:

- View CL&P's planned scheduled date.
- View the status on job requirements such as municipal inspection approvals and easements.
- Identify the CL&P Job Designer assigned to the request.
- Access all of your requests for electric service 24/7.

Registering is free and easy.

1. Visit “For My Business” on www.cl-p.com.
2. Click on Service Request for Contractors
3. Follow instruction on “How to Register”.

Request for Electric

www.cl-p.com

For assistance or more information, call CL&P's New Service Clearing Desk at 1-888-LIGHTCO (1-888-544-4826) or email us at:

CL&PSVC@NU.com

SECTION 7: Third Party Attachments to CL&P Distribution System Facilities

A. Scope

This section addresses the requirements for the attachment of third party equipment to CL&P distribution system facilities. These devices, both pole mounted and pad mounted, are powered by 120 volt AC as their normal power source and are equipped with auxiliary power sources, either batteries or generators, utilized when the normal source is not available. This does not address the installation of communication antennas installed on or near transmission structures. Such installations are covered in a separate guideline entitled, *"NU General Guidelines for Communication Antennas Proposed On or Near Electric Transmission Structures"*.

All Third Parties who propose to install generation and operate in parallel with the CL&P distribution system must follow a formal procedure by submitting an application to start the process, and by complying with the "CL&P & UI Guidelines for Generator Interconnections" dated 12/21/2007, which has been approved by the Connecticut Department of Public Utility Control.

CL&P will assign a Company Facilitator who will serve as the primary point of contact for any interconnection of Generation Facilities to the CL&P distribution system.

Interested parties can obtain copies of the Guidelines, information, and can process the application at the CL&P web site: **www.cl-p.com**. Select "Generator Interconnections".

B. General

1. A Service Request shall be made for each installation.
2. CL&P, telephone, and third party company representatives should agree on the particular location of this equipment. Remote or enclosed metered sites and access roads to these sites must be accessible for meter reading.
3. Installations shall be in compliance with the National Electrical Safety Code (NESC). This equipment shall be

inspected by the municipal inspection authority unless the third party company is regulated by Department of Public Utility Control (DPUC).

4. Requests for installation of equipment on CL&P property shall be directed to the NU Manager of Real Estate Operations. Please call (860) 665-6173 or write to the Real Estate Department, Northeast Utilities, 107 Selden Street, Berlin, CT 06037.

C. Protection Issues

Third party company equipment utilizing generators, batteries, inverters or rectifiers are possible devices of backfeed into the CL&P distribution system. All steps to prevent any and all backfeeds shall be taken:

1. **No equipment shall be connected to the CL&P distribution system without prior approval and testing by CL&P personnel to ensure that backfeed will not occur.** Equipment with permanently connected generators and inverters shall have an automatic, positive, and fail safe method to prevent backfeed. Equipment which demonstrates backfeed capability must be modified by the third party company prior to connection to the CL&P distribution system. This restriction applies to both new and existing installations.
2. A break-before-make transfer switch or cable removal before connection to portable generators is required.
3. The third party company requesting service may have more than one design of backup supply furnished by either the same or several suppliers. The specifications for each model shall be submitted to our Protection and Controls Engineering Department, to determine if backfeed could occur and if so, what protective devices shall be required. This model approval shall be determined by specific test required and witnessed by NU System Engineering and Test Department personnel. The tests shall be performed by the third party company at their expense. Any modifications to previously approved models which may permit backfeed

must be reported by the third party company to NU. A list of approved devices for communications equipment applications is provided at the end of this section.

4. The third party company is responsible for protecting its equipment from faults or abnormal voltages within its facilities and on the CL&P distribution system. CL&P shall not be responsible for damaging fault currents or voltages to the third party company's equipment.
5. CL&P shall be held harmless for damages to third party company equipment resulting from transients due to lightning strikes, load swings, faults, capacitor switching, system switching, etc.
6. CL&P may reduce its voltage level up to an additional 5% during times of system capacity emergency or during designated test periods. The third party company may wish to ensure that this action will cause no adverse effect on its equipment or operation.
7. The interconnection of the third party company's facilities with the CL&P distribution system shall not cause any reduction in the quality of service being provided to our customers. The third party company shall adhere to IEEE Standard 519 for harmonics.
8. CL&P recommends that the third party company install suitable surge arresters on both the source-side and load-side of its system.
9. The third party company shall ensure that any overcurrent protective device on its system coordinates with CL&P primary and/or secondary protective devices. Each third party company shall submit its overcurrent characteristics to System Engineering for review and approval.

D. Metering

1. Services to power supplies shall be single phase, three wire and shall be metered, unless the service meets the requirements for unmetered services.

2. Pad mounted meter units shall not be installed below the 5 foot level without the approval of the Meter Department.
3. All pole mounted installations and the orientation of the meter socket must be approved by CL&P prior to installation.
4. Meters shall not be installed on poles unless the control unit itself is also installed on the pole. The meter location for pole mounted control units should be at the 5 foot level.
5. An approved lever operated manual bypass is required on sockets. 100 amp sockets may be supplied with non-locking jaws. Sockets greater than 100 amps must be supplied with locking jaws.
6. Grounds shall not be installed in meter sockets.
7. A minimum 3 inch conduit with slip joint is required when the service is underground.

E. Grounding

1. The control cabinets and messengers on the pole shall be grounded and bonded to the CL&P grounds and messengers.
2. This bonding shall be an irreversible connection and made at the time of installation by the third party company. The attachment point of the bond to the utility pole ground shall be no higher than the communication gain level.
3. If our primary supply circuit is delta or uni-ground connected, the bonding shall be to the secondary ground, and not to the primary equipment/arrester ground. Do not bond to utility grounds on any pole where transformers, arresters, or any other primary equipment is installed.

F. Pole Mounted Equipment

The NESC requirements for clearance heights above ground shall be followed. The 1997 NESC requirement for effectively grounded equipment cases is 15 feet minimum over roads and areas subject to vehicular traffic and 11 feet over ways subject to pedestrians and

restricted vehicular traffic. There is an exception for effectively grounded equipment cases such as control boxes which allows the equipment to be mounted at a lower level for accessibility "provided such cases do not unduly obstruct a walkway". In addition to the above requirements, the following restrictions apply:

1. CL&P, telephone and third party company representatives should agree on the specific location of this equipment.
2. Equipment exceeding a height dimension of 2 feet shall not be installed on poles that cannot be accessed by aerial device vehicles.
3. Equipment exceeding 16 inches in width shall not be installed on riser poles.

MANUF.	MODEL/DESCRIPTION
Various	Pole mounted rectifier and battery only, with 120 Vac input. With break-before-make switch for portable generator connection. Typically existing units.
Alpha	LE-2 - Natural gas only, pad mounted generator and power supply – 1350 W/15 Amps and 2200 W/20 Amps. With break-before-make plug-receptacle for portable generator connection.
Alpha	LE-2G - Natural gas or propane, pad mounted generator and power supply – 1350 W/15 Amps and 2200 W/20 Amps. With break-before-make plug receptacle for portable generator connection.
Alpha	CE6 - Low profile pad mounted power supply with separate pad mounted generator – 1350 W/15 Amps and 220 W/20 Amps. With break-before-make plug receptacle with portable generator connection.
Alpha	CE7 - Pole or pad mounted unit with separate pad mounted generator - 1350 W/15 Amps and 2200 W/20 Amps. With break-before-make plug receptacle for portable generator connection.
Alpha	XM6015 - Pole or pad mounted, battery/inverter only, 120 Vac input, 60 Vac/15 Amps output. With break-before-make plug receptacle for portable generator connection.
Lectro ZTT	XM9015 - Pole or pad mounted battery/inverter only, 120 Vac input, 90 Vac/15 Amps output. With break-before-make plug receptacle for portable generator connection.
Lectro ZTT	Z3615-X21-CTI – Pole or pad mounted, battery /inverter only, 120 Vac input, 60 Vac/15 Amps output. With break-before-make plug receptacle for portable generator connection.
Ascension Tech.	SS01-MP – 300W, 120/240 Single Phase Inverter
Trace Engr.	ST1000, ST1500, ST2000, ST2500 – 1000W, 1500W, 2000W, 2500W Single Phase 120/240V Inverters

MANUF.	MODEL/DESCRIPTION
Adv. Energy	GC1000 – 1000W, 120/240V Single Phase Inverter GC-1000-SA – 1000W, 120V Single Phase Inverter MM-3000 – 3000W, 120V Single Phase Inverter MM-5000 – 5000W, 120V Single Phase Inverter
Capstone Turbine	330 MicroTurbine – 30kW, 480V, Three Phase Micro Turbine
SMA America	SWR-2500U – 2500W, 208/240 V Single Phase Inverter
Plug Power	SUIPCM 059622 – 6500W, 240V Single Phase Fuel Cell Inverter MP-5000 – 5000W, 120V Single Phase Inverter
Schweitzer	SEL-351A00H24552XX – Utility Interacting Relay, Single-phase & three-phase
Beckwith Electric	M-3410, M-3410A, M-3520 – Intertie/Generator Protection Relay
Capstone Turbine	C60 MicroTurbine – 60kW, 480V, Three Phase MicroTurbine
Xantrex Tech.	SW4024 Series 2, SW4048 Series 2, SW5548 Series 2 (All with Grid Tie Interface accessory) – 4000W, 5500W, 120V, Single Phase Inverters
Xantrex Tech	STXR1500, STXR2000, STXR2500 – 1500W, 2000W, 2500W 240V Single Phase Inverters
Tecogen, Inc.	CM-60, CM-75 – 60Kw, 75Kw 460V or 208/230V Cogeneration Systems
SMA America	SWR-1800U – 1800W, 120 V Single Phase Inverter
Beacon Power	M5 – 5kW, 120V Single Phase Power Conversion System
Fronius USA	IG 2000 – 2kW, 3kW, 240V Single Phase Inverters IG 2500 – 2.5kW, 208V Single Phase Inverter

*The employees of the CT Light & Power
Company want to remind you to
WORK SAFELY!*

SECTION 8: Meter Installation

A. General

1. **UNDER NO CIRCUMSTANCES WILL ELECTRICITY BE SUPPLIED WITHOUT BEING METERED. CONTRACTORS ARE NOT ALLOWED TO INSTALL JUMPERS ON COMMERCIAL/INDUSTRIAL OR NEW RESIDENTIAL SERVICES. JUMPERS ARE ALLOWED ON RESIDENTIAL SERVICE UPGRADES ONLY IF ALL REQUIREMENTS OF THE CUT AND RECONNECT POLICY ARE MET. REFER TO SECTION 2.**
2. You shall furnish, install, own and maintain the meter socket and the instrument transformer enclosure if required.
3. We will furnish, own and maintain all metering equipment.
4. **For all multiple meter installations, each house, store, office, apartment, or area serviced must be permanently marked on the door with its unique identification.** This unique, permanent identification must be indelibly marked on the associated meter socket, on meter cover and load disconnect before the meter will be installed, to avoid billing errors.
5. All self-contained meter sockets shall have ringless covers and must be included in our list of approved equipment. (See Section 12, Approved Metering Equipment.)
6. Primary metering and totalized metering are not a customer option. It may be allowed, under special conditions, if approved by Meter Engineering staff.
7. The meter socket shall not be used as a junction box.

B. Standard Meter Installations

1. The two types of standard metering installations are:
 - self-contained
 - instrument transformer

2. The type of meter installation is determined by the voltage, phase, and total name plate rating of the associated disconnect(s). Refer to Table A on page 15 of this section.


C. Meter Locations

1. WE WILL DESIGNATE METER LOCATIONS FOR NEW OR CHANGED INSTALLATIONS.

- All residential meters shall be located outdoors on the front or side of the structure. The front is considered to be the side adjacent to our distribution facilities.
 - **Commercial meters shall be located outdoors.** Any deviation from this requires pre-installation approval from the CL&P Meter Service Department.
 - Meters shall be grouped so as to keep the number of metering points at a minimum.
 - Instrument transformer enclosures may be located indoors in a suitable area readily accessible to us.
2. You shall maintain a clear, safe work space directly in front of each meter location and a suitable approach to it. Such work space shall be at least 4 feet wide, shall extend out from the meter at least 3 feet, and up to a height of at least 6 feet. In addition, the meter socket must be located at least 3 feet measured horizontally from a gas meter, regulator, propane cylinder or any other fuel storage vessel.
 3. In areas where meter equipment is subject to vehicular traffic, doors, etc. you will be required to install additional protection, such as bollards.
 4. Private property pole-mounted meters are permitted. This is a special installation. Early and detailed consultation with us is required. See Section 11, Figure 13, (page 16) for overhead and Section 11, Figure 14, (page 17) for a conduit system.

NOTICE

Please keep shrubs, debris, fences, and other structures clear of this area. A clearance of 4' wide X 3' deep X 6' high is required.



Do not tamper with the meter, its seals, or connections under penalty of law.

MFR I.D./DATE

5. Private property metering pedestals for a conduit service are permitted. Early and detailed consultation with us is required. Section 11, Figure 15 (page 18) and Figure 16 (page 19).

D. Meter Equipment Mounting and Supports

1. Meter sockets shall be mounted plumb and securely fastened to a permanent rigid wall. Section 11, Figure 10 (page 13). Rust-resistant sheet metal screws of sufficient size shall be used to hold the socket secure. Standard expansion bolts or anchors shall be used on masonry.
2. An individual meter, or meters mounted adjacent to each other horizontally, shall be installed so that the center is approximately 5 feet from the floor or final grade. Section 11, Figure 19 (page 22) and Figure 20 (page 23).
3. Height requirements for vertically positioned, multiple meter installations are:
 - a. Maximum height at top of meter is 6 feet.
 - b. Minimum height at bottom of meter is 2 feet from the floor or finished grade.
 - c. Meter sockets may be attached to adequately braced panels or frames in metal enclosures. With our specific approval, meters may be installed on pre-punched sheet metal panels to be provided by you in metal enclosure.
4. Meter sockets should be mounted on the finished surface of the building or structure. Consult with CL&P for recessed or other non-surface mounted installations.

E. Grounding

1. The grounding electrode conductor connection shall be made at an accessible location in the service equipment and not in the meter socket. **The grounding electrode conductor shall not be run through the meter socket.**
2. The requirements of the Code shall be followed relative to grounding practices.

3. Your service entrance installation shall have a neutral or identified phase conductor which is grounded as required by Code.
4. To avoid corrosion problems, we strongly recommend the use of copper for your grounding conductor.
5. Copper and aluminum shall never be in physical contact with each other. Where electrical connection is necessary, use special devices designed for this purpose.
6. The grounding conductor shall not be connected to any part of a gas or fuel oil system.
7. The meter socket shall not be used as a grounding point.

F. Cover Plates

After the meter socket has been installed, it is your responsibility to protect the interior of the socket by installing an approved optically clear cover obtained from the local inspector or us.

G. Meter and Equipment Seals

1. All meters and all points of access to unmetered wiring on your premises shall have sealing provisions. All disconnecting switches over 400 amps must have locking provisions for CL&P.
2. The breaking of our seals, connecting, disconnecting or tampering with our metering equipment by unauthorized persons is **strictly prohibited**. The law provides penalties for theft of electricity.
3. If it becomes necessary to gain access to any of this sealed equipment, you shall contact us to receive permission to do so. At that time, we will make arrangements to reseal the installation.

H. Self-Contained Single-Phase Meter Installations

Refer to Table A, page 15 of this Section for services where this type of meter installation is required.

1. **Metering Equipment**
 - a. **You shall furnish, install, own and maintain approved, single-phase ringless meter sockets with factory installed bypass.** Our approved sockets are listed in Section 12.

- b. We will furnish, install, own and maintain the electric meter.
- c. Where damage occurs or is anticipated, outdoor socket meters shall be protected by a suitable metal enclosure with locking provisions. We will determine if a protective enclosure is required. This enclosure shall be furnished, installed, owned and maintained by you. We will provide the lock.

2. Sequence of Meter and Service Equipment for Single-Phase Installations.

Single-phase service equipment shall be installed on the load side of self-contained meters except on network systems. Section 11, Figure 17 (page 20) and Figure 25 (page 28). For services fed from a network system the main disconnect with overcurrent protection shall be installed on the line side of the meter (cold sequence).

3. Meter Socket Connections

Line-side conductors are always connected to the top terminals of meter sockets and the load side conductors to the bottom terminals. Section 11, Figure 17 (page 20) Service conductors for all underground-fed meter sockets shall enter from the bottom left knockout. Section 11, Figure 10 (page 13)

4. Grouped Metering

Custom-made installations and modular panels may be used for groups of meters, such as in apartment houses. Prints of these arrangements must be submitted to us and approved by us **prior to installation**. Section 11, Figure 18 (page 21) As an alternative, you may furnish, install, own and maintain a suitable wiring trough with sealing provisions to feed multiple installations of meter sockets. Section 11, Figure 19, (page 22) and Figure 20 (page 23)

5. Metering for Mobile Homes, Campgrounds, and Marinas

- a. Mobile home metering facilities shall be provided by the owner on permanent supports not physically attached to the home. The supports shall be adequate for one or more meter

installation and shall be set at a 4 foot minimum depth. They shall be galvanized steel set in concrete. Section 11, Figure 19 (page 22)

An exception may be allowed for mobile homes permanently installed on a foundation and approved by the local municipal authority. In this case, all requirements for a normal, permanent service apply.

b. We will not provide individual metered services to locations in campgrounds and marinas used for transient purposes.

c. Services for mobile homes, marinas and campgrounds shall be 120/240 volts.

I. Self-Contained Three-Phase Meter Installations

Refer to Table A, page 15 of this Section for services where this type of meter installation is required.

1. Metering Equipment

a. You shall furnish, install, own and maintain approved, three-phase ringless sockets with factory-installed lever-operated bypass and jaw release, complete with flash shield and sealing provision for all three-phase self-contained installations shown in Table A, page 15 of this Section. Refer to Section 12 for approved meter sockets.

b. We will furnish, install, own and maintain the electric meter.

c. Where damage occurs or is anticipated, outdoor socket meters shall be protected by a suitable metal enclosure with locking provisions. We will determine if a protective enclosure is required. This enclosure shall be furnished, installed, owned and maintained by you. We will provide the lock.

2. Sequence of Meter and Service Equipment for Three-Phase Installations

All service equipment shall be installed on the load side of the self-contained meters, unless otherwise specifically approved or requested by us. Section 11, Figure 10 (page 13) and Figure 12 (page 15). **The following exceptions are installations where the**

main disconnect with overcurrent protection shall be installed on the line side of the meter (cold sequence).

- a. All 480 volt services. Section 11, Figure 11 (page 14) and Figure 12 (page 15)**
- b. All services fed from a CL&P network system.**
 - Contact us for detailed requirements, such as R type fuses, 100,000 amp fault current rating, and rejection clips. Section 11, Figure 11 (page 14) and Figure 12 (page 15)**

3. Meter Socket Connections

Line side conductors are always connected to the top terminals of meter sockets and the load-side conductors to the bottom terminals. Section 11, Figure 21 (page 24) Service conductors for all underground-fed meter sockets shall enter from the bottom left knockout. Section 11, Figure 10 (page 13)

J. Instrument (Current and Voltage) Transformer Installations

Refer to Table A, page 18 of this Section for services where this type of meter installation is required.

Every installation which may require instrument transformers shall be referred to us for approval before work is started. See Section 6.

Dedicated 400 Amp services for fire pumps may be an instrument transformer installation to allow the main building and fire pump disconnects and meters to be in the same locations. Meter sockets for fire pumps must be labeled as such.

Your service will not be energized until the metering equipment has been inspected and approved by us.

1. Metering Equipment - Instrument Transformer Enclosure/Conduit/Socket

- a. You shall furnish, install, own and maintain a metal enclosure for the instrument transformers, approved by us. This enclosure shall have provisions for a CL&P lock. Current and voltage (when required) transformers shall be installed in the same compartment. Refer to Section 12, item 7, (page 6) for transformer requirements.**

All meters and all points of access to unmetered wiring on your premises shall have sealing provisions. All disconnecting switches over 400 amps must have locking provisions for CL&P. This enclosure may be:

- 1) an individual cabinet for instrument transformers only, or
 - 2) a combined entrance switch and instrument transformer enclosure with barriers to isolate the two compartments, Section 11, Figure 24 (page 27) and Figure 25 (page 28), or
 - 3) A separate compartment in a metal-enclosed switch gear enclosure built from your prints, which we have previously approved. Such enclosures shall include barriers to isolate the instrument transformer compartment. Wiring in the instrument transformer enclosure shall be limited to that pertinent to the meter installation.
- b. **You shall furnish, install, own and maintain an approved, pre-wired combination meter socket and test switch. Entry through the hub opening at the top of the meter socket is not allowed. See Section 12 for approved equipment. Section 11, Figure 22 (page 25), Figure 24 (page 27) and Figure 25 (page 28, 29)**
- c. You shall furnish, install, own and maintain approved conduit of specified size, minimum 1-1/2 inch, between the instrument transformer enclosures and the combination meter socket. The conduit must be continuous from the instrument transformer enclosure to the side or bottom of the meter socket test switch enclosure. The conduit must be a minimum of 6 inches and a maximum of 50 feet in length. When PVC conduit is used you shall install a separate equipment grounding conductor in this conduit according to the Code. Section 11, Figure 22 (page 25), Figure 24 (page 27) and Figure 25 (page 28, 29)

2. Meter, Instrument Transformers, Test Switch, Wiring Installation

- a. **We shall:**
- Furnish, install, own and maintain the primary conductors for the voltage transformer connections.

- Maintain the test switch and instrument transformers.
- Furnish, install, own and maintain the electric meter.
- Provide, for you to install, the instrument transformers.
- Furnish, install, own and maintain the secondary conductors between the instrument transformers and the test switch.

b. You shall:

- Pick up the instrument transformers from us. CL&P Office locations are listed in the front of this book.
- Provide an approved enclosure with adequate support and clearances for the current and voltage transformers and the service conductors.
- Install current transformers. **The secondary shorting devices on each transformer must be left in the closed position.** Section 11, Figure 23 (page 26)
- Connect line conductors to the current transformers so that the polarity mark on the current transformer is on the line side. Use approved connectors Section 11, Figure 23 (page 26) On 480/277 volt service, install the voltage transformers and current transformers. Section 11, Figure 23 (page 26)

- c.** The connection of your equipment to or before the meter or to the secondary of the instrument transformers is prohibited. Any exceptions to this requirement must be approved by the local Meter Department.

3. Sequence of Meter and Service Equipment

- a.** For instrument transformer installations, you shall furnish, install, own and maintain a main switch or circuit breaker, for your load only, to be located on the line side of the instrument transformers. Section 11, Figure 24 (page 27) and Figure 25 (page 28, 29) This is referred to as cold sequence.

For all other installations, we may grant an exception to the sequence. **Any exception will require review and written approval from us prior to the start of work.** The following are required:

- The power transformer(s) supplying your load will be used to supply only your current load and any other future load(s) as determined by us.
- In accordance with our standards, we furnish, install, own and maintain a primary supply load break device ahead of the power transformer(s) which will allow interrupting the supply to your load without affecting the supply to other customers' loads. In spot network installations, network protectors may be used for this purpose.
- Your installation conforms to all Code requirements.

Submit your request for an exception to us early in your planning stage so that we can determine if the proposed installation will be approved.

K. Gold Service Options

1. If required, the customer shall provide a telephone line as required by the applicable rate.
2. The following telemetering options are available:

Option 1: Phone Automatic Meter Reading (AMR)

This very reliable option, which uses a dedicated telephone line, enables us to remotely read and collect your monthly billing determinates. The meter can also record load profile data – in intervals of 15 minutes.

Over time, this data will build an excellent profile of your load. The data from this accurate load profile is then provided to ISO New England (instead of estimated hourly data).

Should the ability to access and communicate with the recording meter be lost, CL&P would revert to an estimation process for the reporting of your load to ISO New England.

This option allows customers or energy suppliers to choose their billing cycle or specific monthly billing date (i.e., first day of the month, end of the month, 15th of each month or some other monthly schedule).

This option requires a dedicated, direct-dialed, and analog-type telephone line and RJ-11 jack, situated within 3" of the meter socket. The telephone line must be in working order with an assigned telephone number written legibly on the RJ-11 jack. This telephone number must be given to CL&P before a Phone AMR meter is installed. See our [Fee Schedules](#) for more information.

For an approved fee, CL&P will acquire, own, install and maintain the appropriate telephone access recording meter (phone AMR meter) and a meter interface enclosure. CL&P will relocate the RJ-11 telephone jack to be within the interface enclosure at the time of installation.

For some special meter types (normally involving co-generators, distributed resources, etc.), an RJ31X jack or DSL modem or Ethernet connection may be required for proper meter communications. For locations involving generation, please see Section 10.

Option 2: Load Pulse Outputs

We offer this service to customers or energy suppliers who desire a real-time, analog pulse output from CL&P's meter.

This meter has the ability to output load pulses that provide real-time, analog customer load information. Customers or energy suppliers may use this output to interface with their own energy monitoring or management systems, or with external telephone access recording equipment. Section 11, figure 26 (page 30)

For an approved fee, CL&P will acquire and install the appropriate Load Pulse metering equipment and meter interface enclosure. This real-time Load Pulse output is a dry-contact (Form A) arrangement that provides change of state of contact closure for a specific amount of kilowatt-hours.

Suppliers who choose CL&P load estimation but wish to own their own equipment for bill calculations or other services may purchase a Telemetering hourly recorder from the list of CL&P-approved equipment suppliers. (Contact Meter-Services@nu.com or call 800-882-2768 for a current listing of CL&P-approved Telemetering recorders.) The customer or supplier may choose the actual hourly load reporting by CL&P to ISO-NE in lieu of a load estimation process. You must provide a dedicated, direct-dialed and analog-type telephone line to the recorder

to be accessible by CL&P. Note: both the recorder and the communications line may be removed at any time.

Should the ability to access and communicate with the recorder be lost, CL&P would revert to an estimation process for the reporting of your load to ISO New England.

Option 3: Load Pulse Outputs & Phone AMR

This option provides customers or suppliers with a combination of both the features and advantages of Phone AMR (Option 1) and Load Pulse output (Option 2). The pulse output feature provides the ability to connect into a customer's energy management system. Customers/suppliers must supply a dedicated, direct-dialed phone line. Section 11, Figure 27 (page 31).

Option 99: Special Request Metering

CL&P will work with customers or energy suppliers to integrate new products into their own operations. Customers or energy suppliers may request the installation of a particular meter, or our communications device, as long as it meets all applicable standards and our requirements.

Devices installed on our meter cannot interfere with the operation of the meter.

Communications devices or meters approved for installation by us shall be owned, controlled and maintained by CL&P.

Customers or suppliers shall bear all costs associated with the new product approval process as well as the installation, ownership and maintenance of the communications device or meter.

Customers or suppliers may purchase their own software to access their own meter data.

For further requirements and/or requests for this option, please E-mail: Meter-Services@nu.com or Telephone: (800)-882-2768.

L. Platinum Service Options

CL&P's premier service offers "Phone AMR" customers (option 1 or 3 in [Gold Service Options](#)) daily access to interval data through the internet.

MDATA Online operates through interactive software on the web. Customers pay an annual fee and gain access to their energy usage data via a personalized password and ID. Facility managers can download the information and use it to determine peak demand and manage their long-term energy usage. This is a valuable service for customers preparing for restructuring and comparing licensed suppliers, since suppliers will need to know the hourly demands.

With MDATA Online:

- Get cost-effective access to data with no special software
- See individual meters, accounts, or aggregations
- Download data to Excel, Access, Lotus 1-2-3, or Dbase
- Compare multiple meters, multiple time periods
- Maintain up to three years of historical data
- Use standard web browsers
- View calculated data and daily or monthly demand and usage
- Point and click to select various graphs and reports

How to get Online

Customers or suppliers should contact their CL&P account executives or Meter Operations Support (metersvcs@nu.com).

Table A - Available Metering

Supply Characteristics			Self Contained Metering			Instrument Transformer Metering		
Nominal Voltage	Phase	Wire	Total Name Plate Rating of Disconnects	Reference	Figure	Total Name Plate Rating of Disconnects	Reference	Figure
120/240	1	3	400 Amps and less	Sec 8 pg 7 Item H	Sec 11 Pg 20 Fig 17	Over 400 Amps	Sec 8 Pg 10 Item J	Sec 11 Pg 25-29 Fig 22-25
120/208	1	3	400 Amps and less	Sec 8 pg 7 Item H	Sec 11 Pg 20 Fig 17	Not Available		
208Y/120	3	4	400 Amps and less	Sec 8 pg 8 Item I	Sec 11 Pg 24 Fig 21	Over 400 Amps	Sec 8 Pg 10 Item J	Sec 11 Pg 25-29 Fig 22-25
480Y/277	3	4	400 Amps and less	Sec 8 Pg 8 Item I	Sec 11 Pg 24 Fig 21	Over 400 Amps	Sec 8 Pg 11 Item J	Sec 11 Pg 25-29 Fig 22-25
Fire Pump	3	4	400 Amps and less	Sec 8 pg 8 Item I Sec 6 Pg 2 Item 6	Sec 11 Pg 24 Fig 21	400 Amps or greater	Sec 8 Pg 11 Item J Sec 6 Pg 2 Item 6	Sec 11 Pg 25-29 Fig 22-25

ELECTRICAL CONTRACTORS

Your “Service Requests” are only a >CLICK< away!

Quick and Easy * Self Serve * Convenient and Secure

Electrical Contractors are in control with CL&P's online Request for Electric Service system. Contractors can initiate, submit and monitor the status of a particular request for CL&P electric service, anytime, at www.cl-p.com.

Each electric service request is assigned a unique identification number allowing you to monitor the progress of each service requests. You can:

- View CL&P's planned scheduled date.
- View the status on job requirements such as municipal inspection approvals and easements.
- Identify the CL&P Job Designer assigned to the request.
- Access all of your requests for electric service 24/7.

Registering is free and easy.

1. Visit “For My Business” on www.cl-p.com.
2. Click on Service Request for Contractors
3. Follow instruction on “How to Register”.

Request for Electric

www.cl-p.com

For assistance or more information, call CL&P's New Service Clearing Desk at 1-888-LIGHTCO (1-888-544-4826) or email us at:

CL&PSVC@NU.com

SECTION 9: Your Utilization Equipment

A. General

We reserve the right to disconnect your supply upon proper notice when your equipment interferes with the operation of any components of our system or the electric supply to others. You must consult with us in advance of making any commitments for large motors, welders, x-ray machines, or other equipment which may have a high instantaneous electric demand.

1. The operation of equipment having a relatively high load of short duration, such as welding equipment, x-ray machines, elevators, and compressor motors, may make it necessary for us to install special or larger than usual facilities in order to render satisfactory supply. In such cases, you shall pay an additional charge, over and above the regular rate, based on the cost of the additional facilities required.
2. All loads shall be electrically balanced. On three-phase supply, single-phase loads shall be as evenly divided as possible between each of the phases. On single-phase supply, the load should be evenly divided between the two energized conductors and the neutral.
3. **Street Light equipment not owned by CL&P comes under the jurisdiction of the local building inspectors. Consult local building officials and the National Electrical Code for requirements. Street Light equipment owned by CL&P will follow the requirements of the National Electrical Safety Code.**

B. Motor Installation

1. For most efficient operation, motors over $\frac{3}{4}$ horsepower in size should not be operated on 120 volt systems.

2. You should consult with us to determine if three-phase is available before starting work on purchasing utilization equipment. Three-phase supply is not normally provided for residential use or for commercial and industrial use where all motors are smaller than 7-1/2 horsepower. Exceptions may be made where three-phase is available from existing secondary distribution facilities or where the total load justified three-phase.
3. **Motors should be nameplate rated at 208 volts for use on a 208 volt system. Motors rated at 230 volts may not operate properly on a 208 volt system.**

C. Motor Starting Current

1. The starting current of a motor is much greater than the normal running current. The magnitude differs with the motor size and type. While this starting current exists for only a short time, the frequency with which it occurs is a major cause of supply disturbances.
2. Before installing single-phase motors over 3 horsepower or three-phase motors over 20 horsepower, consult us for assurance of adequate supply.
3. The maximum locked-rotor current anticipated shall be the sum of the starting currents of all motors which are started simultaneously.
4. We will specify motor starting limitations. When required, reduced voltage starters or other devices must be furnished, installed, owned and maintained by you.

D. Motor Protective Devices

1. All motors should be controlled and protected from damage that could be caused by continued operation under abnormal conditions such as single phasing. We are not responsible for equipment damage. **You should consider installing a single phasing protection device on each three-phase motor.**
2. There are advantages to incorporating timed under-voltage relays for motors on certain applications. Due to the normal,

rapid reclosure of our supply circuit breakers, many manual restarts can be avoided by delaying the opening of the motor contactor. Conversely, some devices or processes require disconnection immediately upon loss of voltage in order to protect the operation involved.

E. Power Factor

Where any equipment having low power factor characteristics is installed, it is to your advantage to furnish, install, own and maintain corrective equipment which will result in an overall power factor approaching unity. ***Customers installing capacitors to improve the power factor of their loads should contact us so advice may be given regarding supply system characteristics and essential coordination details.*** This will improve your voltage regulation and reduce the size of the attendant electrical equipment.

F. System Disturbances.

1. Certain electronic equipment, such as computers and micro processors, and some manufacturing processes, are extremely sensitive to and can be damaged by disturbances which are inherent in all supply systems. Therefore, you must furnish, install, own and maintain equipment needed to protect your operations.
2. Secondary lightning (surge) arresters may be furnished, owned, installed and maintained by you on the load side of your protective devices.
3. For single phase self-contained residential meters up to 200 amps, surge protectors may be rented from us under our HomeGuard® Surge Protection Service. Our protective devices will be installed between the meter socket and meter face.

*The employees of the CT Light & Power
Company want to remind you to
WORK SAFELY!*

SECTION 10: Your Alternate Electric Energy Sources

A. OPEN TRANSITION Generation (Standby or Emergency)

When you have on site generation that will never run in parallel with the CL&P system, (called OPEN TRANSITION) you must provide an adequately sized double-throw transfer switch that is on the load side of the main disconnect switch and the metering equipment.

This transfer switch is of a “break before make” style. The transfer switch shall open all ungrounded conductors from either the normal supply or alternate supply before the connection is made to the other supply. The installation shall be in accordance with the requirements of the applicable codes. Section 11, Figure 30 (Page 34)

B. NET METERING

Net metering is a method of measuring the energy consumed and produced by a customer’s generating facility. Net metering allows a customer to reduce the amount of energy purchased from an energy supplier and to provide a value for the excess energy (exported energy to the Grid) produced by your Generator.

The Net Metering Tariff – Rider N is available to the following types of customer generation:

- A Qualifying Facility whose generation is less than 50kW
- All Renewable Resources whose generating capacity is less than 500kW
- Class I Renewable energy resources or Hydropower facility whose generating capacity is less than or equal to 2,000kW

What does Net Metering mean?

A special Net Meter is installed by CL&P. The Net Meter will track the energy that is delivered to you by CL&P and any excess generated produced by you energy received by CL&P.

The Net Meter measures two (2) amounts of energy, the amount supplied by CL&P (or alternate energy supplier) and your excess production:

- The energy supplied by CL&P when your load (consumption) exceeds your amount of generation.
- The energy that is generated by your Generating Facility is used in your house/building first to reduce the amount of supply you receive and purchase from CL&P.
- Excess generation is the energy received by CL&P when your generation exceeds your usage (otherwise known as your "load").
- When you generate more than your load, that energy is sent through the CL&P meter and is measured separately. CL&P will provide a credit or payment for this excess generation (excess sales).
- **Please Note: Under no circumstances shall the generator be interconnected inside the meter socket.**

C. CLOSED TRANSITION Generation

When you are considering any on site generating facilities that will operate, **even for a few cycles**, in parallel with the CL&P system, (CLOSED TRANSITION) you must follow all of the applicable requirements of this booklet in addition to the procedures in the "Guidelines for Generator Interconnection" and file an application. The guidelines apply to any device of any electrical rating producing electrical energy including fuel cells, photovoltaic systems, energy storage technologies and rotating generators powered by wind, steam, water and combustion engines. A copy of the guideline can be found on the CL&P web page (www.cl-p.com) or can be requested by phone or US Mail:

Phone: 1-866-324-4237

Mail: The Connecticut Light and Power Company
Distributed Resources Group
P.O. Box 1409
Hartford, CT 06141-1409

C. Uninterruptible Power Supply (UPS)

If you decide that a UPS is required at your facility, you will install, own, operate and maintain such equipment. Your design and installation must prevent back feed into our system. It is important that you contact us early in the planning process to discuss engineering details and to avoid operational problems between your equipment and ours.

*The employees of the CT Light & Power
Company want to remind you to
WORK SAFELY!*

SECTION 11

Illustrations

FIGURE 1
Temporary Electric Service Conduit System





FIGURE 1 NOTES
Temporary Electric Service, Conduit System

We will install our conductors for a temporary electric service that is erected by you and meets the requirements listed below.

NOTE: All conduit shall be inspected by the local municipal authority prior to backfilling.

1. Location of temporary service timber is to be specified by us.
2. The timber is to be structural grade fir or pine with cross section not less than nominal solid 6" x 6" or two 2" x 8" spiked together on 8" centers.
3. The temporary service timber is to be at least 10 ft. long.
4. The temporary service timber is to be set a min. of 3 ft. in firm ground with well-tamped backfill.
5. There is to be no excavation near the temporary service timber which might reduce its stability.
6. Service cable by us.
7. Approved manual lever operated by-pass meter socket is to be installed approximately 5 ft. above ground.
8. Outdoor type service equipment rated in accordance with NEC Sections 230-79 and 230-90 is to be installed on load side of meter socket and within 12" of approved meter socket. Install ground fault interrupter protection.
9. Ground in accordance with code.
10. Electrical grade Schedule 40 PVC conduit supplied and installed by you. All conduit will be listed and labeled for Direct Buried and above ground use.
11. Pipe strap or clamp.
12. Minimum 3" slip joint required.
13. You will provide and install the caution tape which meets the requirements of Section 16-345-3 of the Regulations of Connecticut State Agencies. This tape shall be red with the following continuous printed warning message printed in black; **"Caution - Electrical Line Buried Below"**
Metallic Foil tape is NOT acceptable.
14. Do not enter or open existing electrical structures such as handholes, transformer pads or switch vaults, when installing the pulling line. Call CL&P at 1-800-286-2000 or 947-2000 in Hartford and ask for the Electric Service Designer in the project area

FIGURE 2
Conduit Service: House End




Note:


1. Provide suitable backfill (no rocks)
2. All conduit shall be inspected by the local municipal authority prior to backfilling.

FIGURE 3
Conduit Service: Supply End

A. Supply From Our Conduit System



B. Supply From Our Overhead System



Note:

1. Provide suitable backfill (no rocks)
2. All conduit shall be inspected by the local municipal authority prior to backfilling.
3. Electric service sweeps shall be located on the pole side away from oncoming traffic.

FIGURE 4
Temporary Service From Overhead System`




FIGURE 4 NOTES

Temporary Service From Overhead



We will deadend our service drop for temporary electric service on a pole or timber which is to be erected by you and is to meet the requirements listed below;

1. Location of temporary service pole is to be specified by us such that the service span does not exceed 125 feet measured from our pole to your pole. If the service drop will not be transferred to a permanent location there will be additional charges.
2. If a timber is used, it is to be structural grade fir or pine with cross section not less than nominal 6" x 6" or four 2" x 6" spiked together on 8" centers.
3. The temporary service pole is to be 20 feet minimum. Additional length may be required in order to provide service drop clearance of 16 feet min. over the road and driveway and 12 feet minimum over other areas.
4. The temporary service pole is to be set a minimum of 4 feet in in firm ground and well compacted backfill.
5. The temporary service pole is to be adequately braced to support at its top both a man on a ladder and a service drop tension of 600 pounds. A minimum of two, 2" x 4" braces at right angles to each other, with one in line with the service drop, are to be installed. Braces are to be well spiked flat against the side of the pole at least 12 ft. above ground and to solidly driven 2" x 4" stakes 3 ft. minimum located a minimum 6 ft. from the service pole.
6. There is to be no excavation near the temporary service pole or its braces which might reduce its stability.

Approved electric service is to be installed to meet the following requirements and to be in accordance with the code(s).


7. A weatherhead is to be installed approximately 12" from top of pole and 14 ft. minimum above ground.
8. Service entrance conductors are to be a minimum 3-wire no. 2 aluminum, securely fastened to the pole.
9. An approved manual lever operated by-pass meter socket is to be installed approximately 5 ft. above ground on the side nearest our pole.
10. Outdoor type service equipment rated in accordance with the NEC is to be installed on load side of meter socket within 12" there of. Ground fault interrupter protection shall also be installed.
11. Ground in accordance with NEC. The grounding conductor electrode connection shall be made at an accessible location in the service equipment and not in the meter socket.

FIGURE 5
Overhead Service



Detail 1


FIGURE 6
Overhead Service Entrance Facilities



Note:

- A. Electrical contractor must mark stud location for CL&P service wire holder.
- B. For service attachment points exceeding 20 ft. in height contact us.


FIGURE 7
Service Mast



Note:


Only power service drop conductors shall be permitted to be attached to a service mast (per NEC Section 230.28).

FIGURE 8
Service Attachments



Notes:


- A. Required for masonry and metal buildings
- B. Will be required for large and/or long services.
(ex. 1/0 service or service greater than 140 ft.)



Note:

Electrical contractor must mark stud location for CL&P service wire holder.


FIGURE 9
Trenching Requirements



Notes:

- A. OSHA standards require that spoils shall be placed 24" from edge of trench.
- B. Suitable backfill shall not contain ash, cinder, shell, frozen material, loose debris or stones larger than 2" max. dimension.
- C. All Electrical grade Schedule 40 PVC conduit will be listed and labeled for Direct Buried and above ground use.
- D. **Horizontal Clearance** - shall be 12 inches minimum or more as necessary to permit access for maintenance of all facilities without damage to the others. This includes private wiring. Fuel (Gas and Oil) and Water Lines shall be no closer than 18 inches in all directions. **Vertical Crossing Clearance** - shall be so constructed and supported that upper facility will not transfer harmful load onto any lower facility. There shall be adequate vertical clearance to permit access for maintenance of all facilities without damage to the others. In general, 12 inches is considered adequate separation, but the parties involved may agree to a lesser separation. Fuel (Gas and Oil) and Water Lines shall be no closer than 18 inches in all directions.
- E. You will provide and install the caution tape which meets the requirements of Section 16-345-3 of the Regulations of Connecticut State Agencies. The tape shall be red polyethylene, 6" wide X 4 mils thick with black lettering of a minimum letter size of 120 Helvetica Light. It shall contain the following continuous printed warning:
"Caution - Electric Line Buried Below"
Metallic Foil tape is NOT acceptable.
- F. All conduit shall be inspected by the local municipal authority prior to backfilling.

FIGURE 10
Self-Contained Meter Socket Sequence and
Mounting Arrangement




1. Weatherproof joint with removable or non-removable hub.
2. Socket shall be mounted plumb. On clapboard shingle siding, socket shall be located on the high point of two clapboards.
3. Slip joint for conduit service shall be installed on left side of meter socket only.

Notes:

- A. All network and 480Y/277 volt services will require a main disconnect ahead of the meter (cold sequence).
- B. Self-contained meter sockets are required for:
 - Single-phase 120/240 volt, 400 amp service entrance capacity or less.
 - Single-phase 120/208 volt, 400 amp service entrance capacity or less.
 - Three-phase 400 amp service entrance capacity or less.
- C. All equipment (except meter) furnished, installed, owned and maintained by you.
- D. Ground at service equipment in accordance with NEC Article 250. The grounding electrode conductor connection shall be made at an accessible location in the service equipment and not in the meter socket. The grounding electrode conductor shall not be run through the meter socket.


FIGURE 11
Sequence of meter and service equipment for
self-contained 208Y/120v Network services
and 480Y/277v services
(Cold Sequence - Refer to section 6.B)



Note:

- A. All wiring beyond the service point installed, owned and maintained by you.
- B. An approved lever operated manual bypass with jaw release and flash shield is required.
- C. Maintain clearances as specified in Section 8.C.2.
- D. Line side disconnect must be adjacent to the meter socket and accessible to CL&P at all times.
- E. Provisions must be made to accommodate CL&P's conductors. A sealable pull box may be required. Consult with CL&P prior to installation.

FIGURE 12
Sequence of meter and service equipment for three-phase
self-contained 208Y/120v Network services
and 480Y/277v services
(Cold Sequence – Refer to section 6.B)




1. Wiring trough with suitable connectors for us to terminate our conductors. Sealing provisions are required.
2. Line side disconnect with over current protection, 400 amps or less.
3. Weatherproof joints.
4. Approved manual lever operated by-pass meter socket.
5. Line, if supply is overhead and total ampacity is 400 amps or less.
6. Line, if supply is conduit system (a slip joint is required .for outside installations)

Notes:

- A. Each area serviced must be permanently marked on the door with its unique, permanent identification. This unique identification must be permanently marked on the associated meter socket, on meter socket cover and inside load center before the meter will be installed.
- B. Maintain clearances as specified in Section 8.C.2.
- C. Line side disconnect must be adjacent to the meter socket and accessible to CL&P at all times.


FIGURE 13
Meter Installation-Private Property Pole
Your Conductors Overhead



Notes:

- A. Only one meter to be installed on pole
- B. Ground at service equipment in accordance with NEC Article 250. The grounding electrode conductor connection shall be made at an accessible location in the service equipment and not in the meter socket. The grounding electrode conductor shall not be run through the meter socket.
- C. **Single-phase 120/208 volt Network, Three-phase 208Y/120 volt Network and Three-phase 480Y/277 volt services shall be cold sequenced.**
- D. The customer is responsible for relocating their equipment if the pole is replaced.

FIGURE 14
Meter Installation-Private Property Pole
Your Conductors Underground



Notes:

- A. Only one meter to be installed on pole.
- B. Ground at service equipment in accordance with NEC Article 250. The grounding electrode conductor connection shall be made at an accessible location in the service equipment and not in the meter socket. The grounding electrode conductor shall not be run through the meter socket.
- C. **Single-phase 120/208 volt Network, Three-phase 208Y/120 volt Network and Three-phase 480Y/277 volt services shall be cold sequenced.**
- D. The customer is responsible for relocating their equipment if the pole is replaced.

FIGURE 15
Permanent Pedestal Service - Site Built
(Manufactured Meter Pedestals May Be Used - Refer To Approval List)




FIGURE 16
Manufactured Pedestal Service
(Typical)






FIGURE 17
Single-Phase: Self-Contained Metering Connections
(Typical)



Notes:

- A. An approved lever operated manual bypass is required on sockets for all commercial/industrial and residential services, 100 amp may be supplied with non-locking jaws, greater than 100 amp must be supplied with locking jaw.
- B. When the fifth terminal kit is used, install a No. 12 copper conductor, with white insulation, between the fifth jaw in the 9 o'clock position and the neutral lug/bar.
- C. **For the Underground manhole areas of Hartford, New London, Stamford, Willimantic and Waterbury:**
 Any new or upgraded service (200 amps or less) in these cities, must have a 5 terminal meter socket installed even if 120/240V service.
- D. A five terminal meter socket is acceptable for a 120/240 volt service.

FIGURE 18
Modular Meter Panels for Group Metering Single-Phase 120/240v or
120/208v Three-Phase 208Y/120v Network Three-Phase 480Y/277v




1. Service load disconnects may be located above, below or beside meter.
2. Individual meter sockets with **individual barriers between meter positions** as well as provisions for seals and barrel locks.
3. Single-phase 120/208 volt Network, Three-phase 208Y/120 volt Network and Three-phase 480Y/277 volt services shall be cold sequenced.

Notes:

- A. For 480Y/277v group metering installations consult your local CL&P office.
- B. Sketch of meter panel arrangements must be submitted to CL&P for approval prior to layout and installation of equipment.
- C. Each store, office, apartment or area serviced must be permanently marked on the door with its unique, permanent identification. This unique identification must be permanently marked on the associated meter socket, on meter socket cover and inside load center before the meter will be installed.
- D. Ground at service equipment in accordance with NEC Article 250. The grounding electrode conductor connection shall be made at an accessible location in the service equipment and not in the meter socket. The grounding electrode conductor shall not be run through the meter socket.
- E. Maximum height at top of meter is 6 ft.
- F. Minimum height at bottom of meter is 2 ft. above floor or finish grade.
- G. An approved lever operated manual bypass is required on sockets for all services.
- H. Meter panels must be protected by barriers if there is a potential for damage by vehicles.

FIGURE 19
Single-Phase: Self-Contained Metering
to Multiple Mobile Homes up to six meters




1. Painted 3/4" exterior plywood meter board.
2. Upper edge trimmed to prevent seepage into laminations.
3. Pre-bussed, gang meter sockets marked inside and on cover of socket with mobile home identification. All new mobile homes intended as a dwelling unit will be supplied with 120/240 volts. (Per NEC Section 550-21).
4. Minimum 6 " space between meter socket and service equipment.
5. Suitable support to be galvanized steel in concrete.
6. Weatherproof joint.
7. Service equipment 200 amp or less for each mobile home marked with mobile home identification.
8. Electrical grade Schedule 40 PVC, or galvanized steel conduit. Refer to us for size. Service may be overhead or underground in conduit. Total installed service entrance capacity shall not exceed 400 amp if fed from an overhead service.
9. UL listed slip joint **with one clamp**.

Notes:

Ground at service equipment in accordance with NEC Article 250. The grounding electrode conductor connection shall be made at an accessible location in the service equipment and not in the meter socket. The grounding electrode conductor shall not be run through the meter socket. Grounding in the center wireway is permissible.

FIGURE 20
Self-Contained Outdoor Meter Socket Installation-
Multi-Position Up To Six Meters




1. Wiring trough with suitable connectors for us to terminate our conductors. Sealing provisions are required.
2. Combination meter socket and disconnect is acceptable.
3. Service equipment, 400 amp or less.
4. Weatherproof joints.
5. Line, if supply is overhead and total ampacity is 400 amps or less.
6. Line, if supply is conduit system.

Notes:

- A. Each store, office, apartment or area serviced must be permanently marked on the door with its unique, permanent identification. This unique identification must be permanently marked on the associated meter socket, on meter socket cover and inside load center before the meter will be installed.
- B. An approved lever operated manual bypass with jaw release and flash shield is required for meter sockets greater than 100 amp. An approved lever operated bypass, non jaw release, with flash shield may be used on a 100 amp meter socket.
- C. Maintain clearances as specified in Section 8.C.2.

FIGURE 21
Three -Phase: Self-Contained Metering Connections




1. An approved lever operated manual bypass with jaw release and flash shield.

Notes:

- A. Ground at service equipment in accordance with NEC Article 250. The grounding electrode conductor connection shall be made at an accessible location in the service equipment and not in the meter socket. The grounding electrode conductor shall not be run through the meter socket.
- B. All three-phase network and 480Y/277 volt services will require a main disconnect with over current protection ahead of the meter (Cold Sequence).

FIGURE 22
Outdoor Instrument Transformer Meter
Socket with Test Switch




1. Approved pre-wired meter socket with test switch.
2. Electrical grade Schedule 40 PVC, galvanized steel conduit to be minimum of 1-1/2" diameter, minimum length 6", maximum length 50 ft. If PVC, provide and install an equipment grounding conductor (No. 10 wire or larger). Conduit is to be installed in the bottom or side of meter socket only - no top feed is allowed.
3. Weatherproof joint.

Notes:

- A. Consult CL&P before starting design of any job where an instrument transformer installation is required.
- B. See Figure 25 for meter and service equipment sequence.


FIGURE 23
Instrument Transformer Connections



Notes:

- A. Instrument transformers are required for the following:
 - All single-phase 120/240 volt over 400 amp service entrance capacity.
 - All three-phase 4 wire over 400 ampere capacity
- B. Where multiple conductors or a single conductor over 500 kcmil is used, refer to list of approved instrument transformer mounting equipment in Section 11.
- C. Install a grounding connector and neutral connector in the Instrument Transformer enclosure.
- D. Service line and load side must be marked or labeled in the instrument transformer compartment.

FIGURE 24
Combination Main Switch and Instrument
Transformer Enclosure
(Cold Sequence – Refer to section 6.B)




1. If located outdoors, enclosure shall be of weatherproof design.
2. Electrical grade Schedule 40 PVC or galvanized steel conduit 1-1/2" min. diameter, 6 " min. length and 50 ft. max. length. If PVC, provide and install an equipment grounding conductor (No. 10 wire or larger).
3. Approved pre-wired meter socket with test switch.
4. Must have a locking provision for the main breaker and instrument transformer enclosure.

Notes:

- A. **Consult CL&P before starting design on any job where an instrument transformer installation is required.**
- B. You will provide the combination main disconnect and instrument transformer enclosure, separated by barriers, conduit for meter wiring, primary connectors for instrument transformers and approved pre-wired combination meter socket with test switch.
- C. Instrument transformers provided by us and installed by you.
- D. If 480/277 volt equipment is installed, provisions must be supplied for mounting voltage transformers in the same compartment as the current transformers.
- E. Service line and load side must be marked or labeled in the instrument transformer compartment.
- F. Conduit must be continuous from the instrument transformer compartment to the test switch compartment.
- G. If PVC, provide and install an equipment grounding conductor (No.10 wire or larger).

FIGURE 25
Instrument Transformer Installation
(Cold Sequence – Refer to section 6.B)



Instrument Transformer Enclosure Requirements:

<u>SERVICE</u>		<u>SIZE</u>		<u>CURRENT</u>	<u>VOLTAGE</u>
<u>NOMINAL VOLTAGE</u>	<u>WIDTH</u>	<u>HEIGHT</u>	<u>DEPTH</u>	<u>TRANSFORMER</u>	<u>TRANSFORMER</u>

Minimum size enclosure with current transformers only (Max. 800 amp):

120/240	36"	36"	10"	2 ea	--
208Y/120	36"	36"	10"	3 ea	--

Minimum size enclosure with current and voltage transformers; mounting provisions are required for voltage transformers (Max. 1200 amp):

480Y/277	48"	48"	10"	3 ea	3 ea
----------	-----	-----	-----	------	------


FIGURE 25 Notes
Instrument Transformer Installation
(Cold Sequence – Refer to section 6.B)

1. Electrical grade Schedule 40 PVC or galvanized steel conduit 1-1/2" min. diameter, 6 " min. length and 50 ft. max. length. If PVC, provide and install an equipment grounding conductor (No. 10 wire or larger).
2. Approved pre-wired meter socket with test switch located outdoors.
3. Must have barrel lock sealing devices for main disconnect and instrument transformer enclosure.

Notes:

- A. CONSULT CL&P BEFORE STARTING DESIGN ON ANY JOB WHERE ANY INSTRUMENT TRANSFORMER INSTALLATION IS REQUIRED.**
- B. You will provide the instrument transformer enclosure, conduit for meter wiring, primary connectors for instrument transformers, and approved combination meter socket with test switch.
- C. Ground at service equipment in accordance with NEC Article 250. The grounding electrode conductor connection shall be made at a accessible location in the service equipment and not in the meter socket. The grounding electrode conductors shall not be run through the meter socket.
- D. Service line and load side must be marked or labeled in the instrument transformer compartment.
- E. Install a grounding connector and neutral connector in the instrument transformer enclosure.
- F. Maintain clearances as specified in Section 8.C.2.
- G. Instrument transformers provided by CL&P and installed by you.
- H. Enclosure to have hinged doors, provisions for seal and padlock and mounting brackets for transformers. If located outdoors, enclosure shall be of weatherproof design.
- I. If 480/277 volt equipment is installed, provisions must be supplied for mounting voltage transformers in the same compartment as the current transformers

FIGURE 26
Telephone AMR Equipment Diagram




NOTE:

- A. For some special meter types (normally involving co-generators, distributed generators etc.), an RJ-31X jack, DSL modem or Ethernet connection may be required for proper meter communication.

Figure 27
Meter Interface Enclosure


(For Phone AMR and/or Load Pulse output options)



NOTE:

- A. For PULSES ONLY and NO Phone AMR, there will ONLY be an LPOP.
- B. Maximum carrier voltage is 30 Volts AC
- C. For Phone AMR ONLY and NO pulses supplied, there will ONLY be a Surge Suppressor & RJ11 jack.
- D. For some special meter types (normally involving co-generators, distributed generators etc.), an RJ-31X jack, DSL modem or Ethernet connection may be required for proper meter communications.

Figure 28
Cell Site Metering Pedestal




DWG#042700DDb

1. Individual meter sockets with individual barriers as well as provisions for seals and barrel locks.
2. Single-phase 120/208 volt Network, Three-phase 208Y/120 volt Network and Three-phase 480Y/277 volt services shall be cold sequenced.

Note:

- A. Utilizing a main disconnect is the preferred installation to allow for additional meters beyond six.
- B. Metering pedestal must be protected by barriers if there is a potential for damage by vehicles..

FIGURE 29
Typical Remote Communications Power Site



Note:

- A. A slip joint is not required provided that the steel conduit is integral with the concrete pad.
- B. Blueprints/Design must be submitted to CL&P for approval **prior** to installation.

FIGURE 30
Typical Transfer Switch Installation
In Conjunction With Your Auxiliary Supply

Consult your local authority for proper wiring procedures.





FIGURE 31
Cold Sequence Metering


A. Self-Contained



400 Amps or less

- Three phase Network System
- Single phase Network System
- Three phase 480Y/277 v.


B. Instrument Transformer Rated



Greater than 400 Amps

- Three phase 480Y/277 v
- Three phase 280Y/120 v
- Single phase 120/240 v

FIGURE 32
Hot Sequence Metering



400 Amps or less

- Three phase 208Y/120 v
- Single phase 120/208 v
- Single phase 120/240 v

SECTION 12

CL&P

Approved Metering Equipment

**Prepared by
The 2005 Metering Equipment
Approval Committee**

Henry J. Cosker
Meter Operations Consultant - Berlin, CT

David D. Benedetto
Meter Operations Consultant - Berlin, CT

Edward H. Lafayette
Meter & Service Supervisor - Hadley, MA

Daniel Dileonardo
Meter & Service Supervisor - Hartford, CT

Kevin E. Ward
Revenue Protection - Berlin, CT

General Requirements

1. Safety will be the number one consideration when approving any metering equipment.
2. All meter sockets must have a UL label. Any modification of a meter socket will void the UL listing and the manufacturer's warranty, making it non-compliant with our approved standards.
3. All self-contained meter sockets must be rated for 600 volts or less.
4. A 400 amp instrument transformer rated service (CT's and/or VT's) is no longer offered. All 400 amp services are required to be self contained and will be metered with a Class 320 meter. Any exception will require the approval of the local meter department.
5. **All self-contained meter sockets must have a lever operated manual bypass, with a receiver bracket and a ringless cover with a 7/16" knockout to accept a Brooks S1000 barrel lock or equivalent.**
6. The lever operated manual bypass is required to be single-handle operated:
 - a. 100 ampere may be supplied with non-jaw release
 - b. 200 ampere and 320 ampere must be supplied with jaw release
7. The non-bypassed, in-service position of the operating mechanism must be visible when the meter is installed. Auxiliary straps or jumpers are not acceptable as bypass devices. It must not be possible to override the bypass by replacing the cover when the operating mechanism handle is in the bypassed position
8. A safety flash shield is required on all self-contained meter positions.
9. Horn-type bypasses are not permitted.
10. Sliding-type bypasses are not permitted.

11. Automatic bypasses are not permitted
12. Basic catalog numbers may have different or additional prefix or suffix numbers or letters indicating variations in hubs, sealing rings, addition of fifth terminal, left or right wiring extensions.
13. Meter sockets for use on any three-wire 120/208-volt service must have a fifth terminal located in the 9 o'clock position, connected to the neutral.

The Cities of Hartford, New London, Stamford, Willimantic and Waterbury: Any new or upgraded service 200 Amps or less must have a 5 terminal meter socket installed, with the 5th terminal connected to the neutral, even if 120/240 volt service. Refer to Section 11, Figure 17 (page 20).

14. Custom-made meter channels and modular metering panels may be used for groups of meters such as in apartment houses. Prints of these panel arrangements must be submitted to the Company District Meter Service Supervisor, and the Company's approval obtained prior to installation. Line side panels must be sealable.
15. All underground single position sockets must be a minimum 16"W x 22"H x 5"D, 200 amp, ringless with line side lugs capable of accepting 350 KCMIL conductors with lever operated jaw release bypass. Sockets will also have a minimum 3-inch knockout to accept a 3-inch slip joint. If a service run is greater than 200 feet contact your local CL&P office. The bottom left side knockout is for line conductors only. Line conductors are on the left side so they won't interfere with the bypass handle. The bottom right side knockout is for load conductors.
16. All group metering units must have sealing provisions and meet minimum and maximum height requirements.
 - a. Maximum height (top of meter) is 72 inches.
 - b. Minimum height above floor 24 inches (bottom of meter) indoor, 24 inches (bottom of meter) from finished grade outdoor.
 - c. All meter positions must have individual covers, and barriers between each meter position.
 - d. All meter positions must have lever operated manual bypass.

- e. Each meter position must have a receiver bracket and ringless cover with a 7/16" knockout to accept a Brooks S1000 barrel lock or equivalent.
- 17. All OH/UG 320-amp meter sockets must have 4-inch knockouts, jaw release lever operated manual bypass, with a receiver bracket and a ringless cover with a 7/16" knockout to accept a Brooks S1000 barrel lock or equivalent.
- 18. Hot sequence metering (6 socket positions or less) is required for single-phase 120/240-volt service.* ▲
- 19. New equipment from manufacturers not listed in this book will be considered for approval. Samples must be submitted to the Metering Equipment Approval Committee
- 20. All meter sockets and switchgear must be properly identified with approved catalog numbers listed in this book.

*** Hot Sequence no main disconnect before meter**
▲ Refer to Sec. 4 Page 1 for service limitations

Requirements for Commercial Metering

- 1. Cold sequence metering is required for all self-contained 480 volt services and all three-phase services fed from a CL&P secondary distribution network grid. Line side disconnect must be adjacent to meter socket and accessible to CL&P at all times. See Section 6.B.3.a and b (page 1), Section 11, Figure 12 (page 15) and Section 11, Figure 11(page 15).*
- 2. Custom-built meter centers must have individual utility approval prior to installation.
- 3. Three-phase four-wire self-contained commercial group metering must have barriers between meter positions.
- 4. Self Contained 480/277 volt group metering must have individual disconnects before each meter position. *
- 5. A 400 amp instrument transformer rated service (CT's and/or VT's) is no longer offered. All 400 amp services are required to be self contained and will be metered with a Class 320 meter.

Any exception will require the approval of the local meter department.

***Cold sequence main disconnect required before metering**

6. Custom-built switchgear with instrument transformer enclosures must have individual utility approval prior to installation. A print of the switchgear must be supplied to the appropriate district meter supervisor. Check with CL&P for available fault current before ordering equipment.
7. Custom-built switchgear instrument transformer compartments must have barriers on all four sides of compartment.
8. All 480/277 volt switchgear with instrument transformer enclosures must have:
 - Provisions for mounting current transformers and voltage transformers in the same compartment with hinged sealable doors.
 - 600 amp - 1600 amp Bar Type current transformers
 - 2000 amp-3000 amp Window Type current transformers.
9. All instrument transformer enclosures for 480/277 volt three-phase four-wire wye services must be 48" W x 48" H x 10" D. All instrument transformer enclosures require hinged double doors and padlock sealing provisions
10. Neutral bus and grounding connections must be available in instrument transformers enclosure
11. Combination circuit breaker and instrument transformer enclosures must have locking provisions for the Main Breaker and Instrument Transformer enclosure.
12. All Main Breakers or Disconnects must have provisions to be locked in the OFF position.
13. Conduit must be continuous from the instrument transformer compartment to the test switch compartment.

SINGLE-PHASE • RESIDENTIAL/COMMERCIAL • OUTDOOR

The following require a lever-operated bypass with flash shield Three-Wire 120/240 Volt and Three-Wire 120/208 Volt
For 120/208 Volt – Requires the 5th Terminal in the 9:00 O'clock position

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Ringless</u>
100 Ampere:			
Cooper B-Line	1	OH	EL12L41GR1N
	2-6	OH/UG	HEC10432CGR1N-HEC10436CGR1N (Horz.)
Cutler Hammer	1	OH	UBT-H4203B-CH
	1	OH	UBT-H4213B-CH
	1	OH	UBT-C4213B-CH
	1	OH	UBGT-H4203B-CH (5 Terminal)
	1	OH	UBGT-H4213B-CH (5 Terminal)
Durham	1	OH	UBT-H4203B
	1	OH	UBT-H4213B
	1	OH	UBT-C4213B
	1	OH	UBGT-H4213B (5 Terminal)
	1	OH	UBGT-H4203B (5 Terminal)
L & G/Siemens	1	OH	40605-01NU
Midwest Electric	1	OH	UBT-H4203-MEP
	1	OH	UBT-H4213B-MEP
	1	OH	UBT-C4213B-MEP
	1	OH	UBGT-H4213B-MEP (5 Terminal)
	1	OH	UBGT-H4203B-MEP (5 Terminal)

100 Ampere: Continued

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Ringless</u>
Milbank	1	OH	U2272-RL-5T9-BL
	2 - 6	OH/UG	U2752-X-5T9 / U2756-X-5T9 (Horz.)
	2 - 3	OH	U5112-X-BL/U5113-X-BL (Vert.)
Square D	1	OH	UBT-H4203B-SQD
	1	OH	UBT-H4213B-SQD
	1	OH	UBT-C4213B-SQD
	1	OH	UBGT-H4203B-SQD (5 Terminal)
	1	OH	UBGT-H4213B-SQD (5 Terminal)

SINGLE-PHASE • RESIDENTIAL • OUTDOOR • CL&P only

Heavy duty block, non-lever bypass, non-locking jaws with flash shield 3-Wire 120/240 Volt and Three-Wire 120/208 Volt
 For 120/208 Volt – Requires the 5th Terminal in the 9:00 O'clock position

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Ringless</u>
200 Ampere: Milbank	1	OH	U5858-RRL-QG-BL-NE
	1	UG	U5857-0-BL-NE

SINGLE-PHASE • RESIDENTIAL/COMMERCIAL • OUTDOOR

The following require a lever-operated bypass with flash shield Three-Wire 120/240 Volt and Three-Wire 120/208 Volt

For 120/208 Volt – Requires the 5th Terminal in the 9:00 O'clock position

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Ringless</u>
200 Ampere:			
Cooper B-Line	1	OH/UG	EL20L45GR1N
	1	OH	EL20L41GR1N
	2-6	OH/UG	HEL20432CGR1N-HEL20436CGR1N (Horz.)
Cutler Hammer	1	OH	UBT-H4203B-CH / UBTE4203BCH
	1	OH	UBT-H4213B-CH / UBTE4213BCH
	1	OH	UBGT-H4203B-CH / UBGT-E4203BCH (5 Terminal)
	1	OH	UBGT-H4213B-CH / UBGT-E4213BCH (5 Terminal)
	1	UG	1007994A-CH / 1007994EACH
	2-6	OH/UG	UBGT-2H42353U / UBGT-6H42393UU-CH (5 Terminal)
	1	UG	1007995A-CH / 1007995EACH (5 Terminal)
Durham	1	OH	UBT-H4203B
	1	OH	UBT-H4213B
	1	OH	UBGT-H4203B (5 Terminal)
	1	OH	UBGT-H4213B(5 Terminal)
	1	UG	1007994A
	2-6	OH/UG	UBGT-2H42353U/ UBGT-6H42393UU (5 Terminal)
	1	UG	1007995A (5 Terminal)
L & G/Siemens	1	OH	40005-OBNU / 40005-01NU
	1	OH/UG	48805-OBNU
	1	OH	S40405-OBNU / S40405-01NU
	1	OH	40405-01NU

200 Ampere Continued:

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Ringless</u>
L & G/Siemens	2-6	OH/UG	40405X-023NU
Midwest Electric	1	OH	UBT-H4213B- MEP
	1	OH	UBGT-H4203B- MEP (5 Terminal)
	1	OH	UBGT-H4213B-MEP (5 Terminal)
	1	UG	1007994A-MEP
	1	UG	1007995A-MEP (5 Terminal)
	2-6	OH/UG	UBGT-2H42353U/ UBGT-6H42393UU-MEP(5 Terminal)
Milbank	1	OH	U9800-RRL-QG-BL
	1	UG	U4721-O-BL
	2-6	OH/UG	U2872-XT-5T9 / U2876-XT-5T9
Murray	1	OH	RH173CRJNU
	1	OH/UG	RH178CRJNU
Square D	1	OH	UBT-H4203B- SQD
	1	OH	UBT-H4213B-SQD
	1	OH	UBGT-H4203B-SQD (5 Terminal)
	1	OH	UBGT-H4213B-SQD (5 Terminal)
	1	UG	1007994A-SQD
	1	UG	1007995A-SQD(5 Terminal)
	2-6	OH/UG	UBGT-2H42353U/ UBGT-6H42393UU-SQD (5Terminal)

METER PEDESTALS

For 120/208 Volt – Requires the 5th Terminal in the 9:00 O'clock position

Single-Phase • Residential/Commercial • All Outdoor Installations Require Lever-Operated Bypass with Flash Shield

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Ringless</u>
200 Ampere:			
Milbank	1	UG	U4322-O-BL
	2	UG	U4323-O-BL

SINGLE-PHASE • RESIDENTIAL/COMMERCIAL • OUTDOOR

The following require a lever-operated bypass with flash shield Three-Wire 120/240 Volt and Three-Wire 120/208 Volt

For 120/208 Volt – Requires the 5th Terminal in the 9:00 O'clock position

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Ringless</u>
320 Ampere:			
Cooper B-Line	1	OH/UG	EL32T45GR1N
Cutler Hammer	1	OH	UBT-H4300T-CH / UBTE4300TCH
	1	OH	UBT-H4309T-CH / UBTE4309TCH
	1	OH/UG	1008068-CH / 1008068ECH
	1	OH	UBTE4300TCH + MSL5T
	1	OH	UBTE4309TCH + MSL5T
Durham	1	OH	UBT-H4300T
	1	OH	UBT-H4309T
	1	OH/UG	1008068
L & G/Siemens	1	OH	S9804-9144
	1	OH/UG	S9804-9146
	1	OH/UG	44704-01NU
	1	OH	47704-01NU

320 Ampere continued:

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Ringless</u>
Midwest Electric	1	OH	UBT-H4300T-MEP
	1	OH/UG	1008068-MEP
	1	OH	UBT-H4309T-MEP
Milbank	1	OH/UG	U4778-X-BL
Murray	1	OH	RK173AHJNU
	1	OH/UG	RK178AHJNU
Square D	1	OH	UBT-H4300T-SQD
	1	OH/UG	1008068-SQD
	1	OH	UBT-H4309T-SQD

SINGLE-PHASE • RESIDENTIAL/COMMERCIAL • OUTDOOR

The following require a lever-operated bypass with flash shield Three-Wire 120/240 Volt and Three-Wire 120/208 Volt

Combination Meter Sockets and Disconnect Devices

For 120/208 Volt – Requires the 5th Terminal in the 9:00 O'clock position

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Ringless</u>
100 Ampere:			
Cooper B-Line	1	OH	ECCB10L24A3GR1N
Milbank	1	OH	U3741-XL-100
Siemens	1	OH	MM0202L1125RLC
200 Ampere:			
Cooper B-Line	1	OH/UG	ELCB20L24A5GR1N
	2-6	OH/UG	VELMP20432LGRST5K9-VELMP20436LGRST5K9 (vertical)
Cutler Hammer	1	OH	CMBXB200BTS

200 Ampere Continued

	1	OH	CMBX3242B200BTS
Milbank	1	OH	U3791N-RXL-200-BL
	1	OH/UG	U5140-200-BL
	2-6	OH/UG	U4372-XT-5T9 / U4376-XT-5T9
Siemens	1	OH/UG	MM0202L1200RLC
	2-6	OH/UG	SP4212RJL/SP6612RJL
320 Ampere:			
Cooper B-Line	1	OH/UG	ELCB32C24A5GR1N
Milbank	1	OH/UG	U4835-X-2\200-BL
Siemens	1	OH/UG	MC0408B1400RLTM
	1	OH/UG	MC0816B1400RLTM
	1	OH/UG	MC0816B1350RLTM
	1	OH/UG	MM0404L1400RLM
	1	OH/UG	JA0408B1400RLTM
	1	OH/UG	JA0816B1400RLTM

THREE-PHASE • COMMERCIAL • OUTDOOR

Must Have Jaw Release Lever-Operated Bypass with Flash Shield

All 480Y/277 volt and three-phase 208Y/120 volt network services require main disconnect before meter (cold sequence) Check with CL&P for available fault current before ordering equipment.

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Four-Wire—Three-Phase 7 Terminal</u>
200 Ampere:			
Cooper B-Line	1	OH	EL20L71GR1N
	1	OH/UG	EL20L75GR1N
Cutler Hammer	1	OH	UBT-H7203B or T – CH / UBTE7203BCH

200 Ampere cont. Cutler/Hammer	1	OH	UBT-H7213B or T – CH / UBTE7203TCH
	1	UG	1007996A-CH / 1007996ECH
	1	OH	UBTE7213BCH / UBTE7213TCH
Durham	1	OH	UBT-H7203B or T
	1	OH	UBT-H7213B or T
	1	UG	1007996A
L & G/Siemens	1	OH	40007-01NU / 40407-01NU
	1	OH/UG	48807-02NU
	2 - 6	OH/UG	40407X-023NU
Midwest Electric	1	OH	UBT-H7203B or T - MEP
	1	OH	UBT-H7213B or T- MEP
	1	UG	1007996A-MEP
Milbank	1	OH	U9700-RRL-QG-BL
	1	UG	4910-O-BL
Murray	1	OH	RH173GRJNU
	1	OH/UG	RH178GRJNU
Square D	1	OH	UBT-H7203B or T - SQD
	1	OH	UBT-H7213B or T- SQD
	1	UG	1007996A-SQD

THREE-PHASE • COMMERCIAL • OUTDOOR

Must Have Jaw Release Lever-Operated Bypass with Flash Shield

All 480Y/277 volt and three-phase 208Y/120 volt network services require main disconnect before meter (cold sequence). Check with CL&P for available fault current before ordering equipment

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Four-Wire—Three-Phase 7 Terminal</u>
320 Ampere:			
Cooper B-Line	1	OH	EL32T75GR1N
Cutler Hammer	1	OH	UBT-H7300T-CH / UBTE7300TCH
	1	OH/UG	1008069-CH / 1008069ECH
Durham	1	OH	UBT-H7300T
	1	OH/UG	1008069
L & G/Siemens	1	OH	S/9804-9145
	1	OH	S/47707-01NU
	1	OH/UG	S/9804-9147
Midwest Electric	1	OH	UBT-H7300T-MEP
	1	OH/UG	1008069-MEP
Milbank	1	OH/UG	U4911-X-BL
Murray	1	OH	RK173GHJNU
	1	OH/UG	RK178GHJNU
Square D	1	OH	UBT-H7300T-SQD
	1	OH/UG	1008069-SQD

THREE-PHASE • COMMERCIAL • OUTDOOR (Cont'd)

Must Have Jaw Release Lever-Operated Bypass with Flash Shield (may also be used on 100 Ampere)
All 480Y/277 volt and three-phase 208Y/120 volt network services require main disconnect before meter (cold sequence). Check with CL&P for available fault current before ordering equipment

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Four-Wire—Three-Phase 7 Terminal</u>
200 Ampere: Combination Meter Sockets and Disconnect Devices			
Cooper B-Line	1	OH/UG	ELCB20L27A5GR1N
Milbank	1	OH	U3781-RXL-200-BL
	1	OH/UG	U5750-200-BL
Siemens	1	OH/UG	MM0303B3200RLC

**THREE-PHASE • COMMERCIAL • OUTDOOR
COLD SEQUENCE COMBINATION METER SOCKETS (BREAKER BEFORE METER)**

Must have Jaw Release Lever-Operated Bypass with Flash Shield.

All 480Y/277 volt and 208Y/120 volt network services require main disconnect before meter (cold sequence). Check with CL&P for available fault current before ordering equipment.

<u>Manufacturer</u>	<u>Number of Positions</u>	<u>Type of Service</u>	<u>Four-Wire-Three-Phase 7 Terminal</u>
200 Ampere:			
Milbank	1	OH	U5767-X-200-CB-BL-NE
	1	UG	U5787-0-200-CB-BL-NE
320 Ampere:			
Milbank	1	OH	U5796-X-400-CB-BL-NE
	1	UG	U5799-0-400-CB-BL-NE

GROUP METERING • SINGLE-PHASE • RESIDENTIAL/COMMERCIAL

Three-Wire 120/240 Volt and Three-Wire 120/208 Volt 100-Amp Lever-Operated Bypass—200-Amp Lever-Operated Jaw Release Bypass with Flash Shield. Refer to General Requirements for Height Restrictions.

For 120/208 Volt – Requires the 5th Terminal in the 9:00 O'clock position

<u>Manufacturer</u>	<u>Series or Number</u>	<u>Type</u>	<u>Ampere Rating</u>			<u>Indoor</u>	<u>Outdoor</u>
			<u>100</u>	<u>200</u>	<u>320</u>		
Cutler Hammer	35MM	Ringless	Yes	Yes	Yes	Yes	Yes
General Electric	Meter Mod III	Ringless	Yes	Yes	Yes	Yes	Yes
Murray	DL	Ringless	Yes	Yes	Yes	Yes	Yes
Siemens	W1MM	Ringless	Yes	Yes	Yes	Yes	Yes
	W2MM	Ringless	Yes	Yes	Yes	Yes	Yes
Square D	EZM	Ringless	Yes	Yes	Yes	Yes	Yes
	MPL Meter PAK	Ringless	Yes	Yes	No	Yes	Yes

GROUP METERING • THREE-PHASE

208Y/120 Volts 100-Amp Lever-Operated Bypass—200-Amp Lever-Operated Jaw Release Bypass with Flash Shield.
Refer to General Requirements for Height Restrictions, Must have Barriers between Meter Positions

<u>Manufacturer</u>	<u>Series or Number</u>	<u>Type</u>	<u>Ampere Rating</u>			<u>Indoor</u>	<u>Outdoor</u>	<u>Bypass</u>
			<u>100</u>	<u>200</u>	<u>320</u>			
Cooper B-Line	HEL20732CGR1N- HEL20736CGR1N	Ringless	Yes	Yes	No	Yes	Yes	Yes
Cutler Hammer	37MM	Ringless	Yes	Yes	Yes	Yes	Yes	Yes
	CCMS	Ringless	Yes	Yes	Yes	Yes	Yes	Yes
General Electric	Meter Mod III	Ringless	Yes	Yes	Yes	Yes	Yes	Yes
Milbank	U2732-XT / U2736-XT	Ringless	Yes	Yes	No	Yes	Yes	Yes
Murray	DL	Ringless	Yes	Yes	Yes	Yes	Yes	Yes
Siemens ITE	W3MM	Ringless	Yes	Yes	Yes	Yes	Yes	Yes
Square D	EZM	Ringless	Yes	Yes	Yes	Yes	Yes	Yes

GROUP METERING • THREE-PHASE

480Y/277 Volts 100-Amp Lever-Operated Bypass—200-Amp Lever-Operated Jaw Release Bypass with Flash Shield
Refer to General Requirements for Height Restrictions. Meter Positions Must be Cold Sequence, Disconnect Breakers
before each Meter Position, Must have Barriers between Meter Positions

<u>Manufacturer</u>	<u>Series or Number</u>	<u>Type</u>	<u>Ampere Rating</u>			<u>Indoor</u>	<u>Outdoor</u>	<u>Bypass</u>
			<u>100</u>	<u>200</u>	<u>320</u>			
Cutler Hammer	PRL-C/CCMS	Ringless	Yes	Yes	Yes	Yes	Yes*	Yes
Siemens	MMS	Ringless	Yes	Yes	Yes	Yes	No	Yes
RSE-Sierra	CUSTOM	Ringless	Yes	Yes	Yes	Yes	No	Yes

*NOTE: NEMA 3R Outdoor Cabinet with Split Door (Top and Bottom Doors) for Meter Access

PRE-WIRED INSTRUMENT TRANSFORMER-RATED SOCKETS WITH PLATED TEST SWITCH

Manufacturer
Cooper B-Line
Milbank
Siemens

6 Terminal Single Phase
SW02062S1GR1N
UC7478-O-81-NOE
9837-0901

Manufacturer
Milbank
Siemens

8 TERMINAL—3-PHASE 3-WIRE
UC7444-O-141-NOE
9837-0902

Manufacturer
Cooper B-Line
Milbank
Siemens

13 TERMINAL—3-PHASE 4-WIRE
SW02132S1GR1N
UC7445-O-311-NOE
9837-0903

GROUP METERING BARRIERS

Manufacturer
Cutler-Hammer
General Electric
Siemens

Square D

Catalog Number
37MMBK
TMBR3
Contact your local Siemens
Representative
MML200BAR

600 – 1600 AMP COMBINATION CIRCUIT BREAKER AND INSTRUMENT TRANSFORMER ENCLOSURE
120/240 Volt and 208Y/120 Volt Services, with BAR TYPE Current Transformers. Check with CL&P for available fault current
before ordering equipment

<u>Manufacturer</u> <u>Rated Voltage</u>	<u>Interruption Duty</u> <u>Amps Sym @</u> <u>Rated Voltage</u>	<u>600 Amp</u>	<u>800 Amp</u>	<u>1,000 Amp</u>	<u>1,200 Amp</u>	<u>1,600 Amp</u>
Cutler Hammer:						
120/240	65,000	WBM	WBM	-	-	-
208Y/120	65,000	WBM	WBM	WBM	WBM	-
East Coast Power Systems:						
120/240	65,000	MBCT65B1	MBCT85B	-	-	-
208Y/120	100,000	MBCT6HB1	MBCT8HB1	MBCT10H81	MBCT12HHB1	MBCT16HHB1
General Electric:						
208Y120	42,000	SE46K6	SE46M8	-	-	-
120/240-						
208Y/120	65,000	SE46HM6	SE46HM8	SE46HKM10 (208Y/120)	SE46HKM12 (208Y/120)	-
Murray:						
120/240	65,000	CBCT636LX	CBCT836M6	-	-	-
208Y/120	100,000	CBCT636HL	CBCT836HM	CBCT1036HN	CBCT1236HN	-
Siemens ITE:						
120/240	65,000	BCT636LXD6	BCT836LMXD6	-	-	-
208Y/120	100,000	BCT636HLD6	BCT836HMD6	BCT1036HND6	BCT1236HND6	-
Square D:						
120/240	65,000	CTC-366CU	CTC-368CU	-	-	-
208Y/120	65,000	CTC-366CU	CTC-368CU	CTC3610CU	CTC3612CU	-
208Y/120	65,000	QED	QED	QED	QED	QED

600 – 1600 AMP COMBINATION CIRCUIT BREAKER AND INSTRUMENT TRANSFORMER ENCLOSURE

480Y/277 Volt Services, Cold Sequence, **BAR TYPE** Current Transformers and Voltage Transformers must be installed
in the same compartment. Check with CL&P for available fault current before ordering equipment

		<u>Interruption Duty</u>				
<u>Manufacturer/</u>	<u>Amps Sym @</u>					
<u>Rated Voltage</u>	<u>Rated Voltage</u>					
		<u>600 Amp</u>	<u>800 Amp</u>	<u>1,000 Amp</u>	<u>1,200 Amp</u>	<u>1,600 Amp</u>
Cutler Hammer:						
480Y/277	65,000	WBM	WBM	WBM	WBM	PRL-C
480Y/277	65,000	PRL-C	PRL-C	PRL-C	PRL-C	PRL-C
East Coast Power Systems:						
480Y/277	35,000	MBCT65B1	-	-	-	-
480Y/277	50,000	MBCT6HB1	MBCT8HB1	MBCT10H81	MBCT1081HB1	MBCT1016HB1
480Y/277	65,000	MBCT6HB1	MBCT8HB1	MBCT10H81	MBCT1081HB1	MBCT1016HB1
General Electric:						
480Y/277	30,000	SE46K6PT	SE46M8PT	SE46KM10PT	SE46KM12PT	-
480Y/277	35,000	SE46HM6PT	SE46HM8PT	SE46HKM10P T	SE46HKM12PT	-
480Y/277	As Specified	Spectra Series AV I, II, III & V	Spectra Series AV I, II, III & V	Spectra Series AV I, II, III & V	Spectra Series AV I, II, III & V	-
RSE-Sierra						
480Y/277	As Specified	Custom	Custom	Custom	Custom	Custom
480Y/277	As Specified	SB	SB	SB	SB	SB
Square D						
480Y/277	65,000	CTC-366CU	CTC-368CU	CTC3610CU	CTC3612CU	-
480Y/277	65,000	QED	QED	QED	QED	QED

**2000/3000 Amp COMBINATION CIRCUIT BREAKER AND INSTRUMENT
TRANSFORMER ENCLOSURE**

480Y/277 Volt Services, Cold Sequence, **WINDOW TYPE** Current Transformers and Voltage Transformers must
be installed in the same compartment. Check with CL&P for available fault current before ordering equipment

<u>Manufacturer/ Rated Voltage</u>	<u>Interruption Duty Amps Sym @ Rated Voltage</u>	<u>2000/3000 Amp</u>
Cutler Hammer: 480Y/277	As Specified	PRL-C
General Electric 480Y/277	As Specified	Spectra Series - AV I, II, III & V
Siemens 480Y/277	As Specified	SB
Square D: 480Y/277	As Specified	QED Series

COMBINATION FUSED ENTRANCE SWITCH AND INSTRUMENT TRANSFORMER ENCLOSURE

120/240 Volt and 208Y/120 Volt Services with BAR TYPE Current Transformers

Check with CL&P for available fault current before ordering equipment

<u>Manufacturer</u>	<u>Rated Voltage</u>	<u>600Amp</u>	<u>800 Amp</u>	<u>1,200 Amp</u>
Cutler Hammer	120/240	WSM	WSM	-
	208Y/120	WSM	WSM	WSM
East Coast Power Systems	120/240	MSCT6B1	MSCT8B1	-
	208Y/120	MSCT6B1	MSCT8B1	MSCT12B1
General Electric	240	FSE426	FSE428	-
Murray	240	FSCT632	FSCT836	-
Siemens	240	SCT632	SCT836	-
Square D	240	QED	QED	QED

COMBINATION FUSED ENTRANCE SWITCH AND INSTRUMENT TRANSFORMER ENCLOSURE

480Y/277 Volt Services, Cold Sequence, BAR TYPE Current Transformers and Voltage Transformers
must be installed in the same compartment.

Check with CL&P for available fault current before ordering equipment

<u>Manufacturer</u>	<u>Rated Voltage</u>	<u>600Amp</u>	<u>800 Amp</u>	<u>1,200 Amp</u>
Cutler Hammer	480Y/277	CCMS	CCMS	CCMS
East Coast Power Systems	480Y/277	MSCT46B1	MSCT48B1	MSCT412B1
General Electric	480Y/277	FSE446PT	FSE448PT	FSE4412GFPT
Murray	480Y/277	SB	SB	SB
Siemens	480Y/277	SB	SB	SB
Square D	480Y/277	QED	QED	QED

In addition to 480 volt services any 600 volt services must have integral mounting provisions in the instrument transformer compartment for current transformer and voltage transformers.

INSTRUMENT TRANSFORMER MOUNTING EQUIPMENT IN SEALABLE ENCLOSURE WITH HINGED DOORS

For use when Parallel Phase conductors are used or when Phase Conductors are larger than 500 KC MIL

Bar Type Current Transformers are used in these Enclosures

Cabinets for use on 480Y/277 services must have provisions for mounting CT's and VT's

<u>Manufacturer</u>	<u>Rated Voltage</u>	<u>Series or Number</u>	<u>Dimensions</u>	<u>Service Size</u>
Cooper B-Line	208Y/120	363612DDHRTCT1N	36"W x 36"H X12"D	400 & 800 Amp
	208Y/120-480Y/277	484814DDHRTCT1N	48"W X 48"H X 14"D	800 Amp
East Coast Power Systems	208Y/120	CTN800	36"W x 36"H X12"D	400 & 800 Amp
	208Y/120-480Y/277	CTN1200	48:W X 48"H X10"D	800 & 1200 Amp
Milbank	208Y/120	S1855-O	36"W x 36"H x 12"D	400 & 800 Amp
	208Y/120-480Y/277	S1856-O	48"W x 48"H x 12"D	800 & 1200 Amp
Hoffman	208Y/120	A800NECT	36"W x 36"H x 12"D	400 & 800 Amp
	208Y/120-480Y/277	A1200NECT	48"W x 48"H x 12"D	800 & 1200 Amp

SECTION 13: Index

A	<u>Section</u>	<u>Item</u>	<u>Page</u>
Access	1	G	5
AMR (Definition)			
Antennas	1	A.10	2
Approvals	1	C.1	3
Approved Metering Equipment	12		
B			
Banners	1	A.11	2
C			
Campgrounds	4	A.3.b	1
Checklist:			
New Services	12		6
Service Changes (Upgrades)	12		7
Instrument Transformer	12		8
Clearance	3	D.1.a	1
Clearing Desk (Definitions)			
Codes (Definitions)			
Conduit System (Definition)			
Connections (Meter Socket)	8	I.3	
Connections (to our facilities)	5	A.4	1
Cost of Service Facilities	5	A.4	1
Cover Plates	8	F	
Current Transformers	8	J	
Cut and Reconnect	2		
D			
Damage to Meters	8	H.1.c	
Definitions			
Demolition	5	F.1	2
Digging	1	A.3	1
Disconnecting	5	D	2
Disconnecting Service	5	D	<u>2</u>

	<u>Section</u>	<u>Item</u>	<u>Page</u>
E			
Emergency Generation	10	A	1
Employee Identification	1	J	6
Extended Metering Options	8	K	
F			
Fire Pumps	6	B.6	2
Frequency (See Hertz)	4	A.1	1
Fuse Main	6	C.1	2
G			
Ground Faults	1	A.8	1
Grounding	8	E	
Group Metering	8	H.4	
H			
Hertz	4	A.1	1
I			
Identification:			
Employee	1	K	6
Contractor/Electrician	6	E	3
Inspections	1	J	6
Instrument Transformers	8	J	
Interrupter, Ground Fault	1	A.8	1
L			
Lateral (Definition)			
Limiter	6	B.4	1
Load Pulse Outputs	8	K.2	
Location Weatherhead	3	D	1-2
M			
Main Fuse	6	C.1	2
Marinas	8	H.6	

	<u>Section</u>	<u>Item</u>	<u>Page</u>
Meter(s) Installation:	8	B	
Location	8	C	
Grouped	8	H.4	
Sockets	8	D.4	
Sequence (Definition)			
Sequence	8	H.2	
Mobile Homes	8	H.6	
Motors	9	B-D	1-3
Metering Transformers	8	J	
(See Instrument Transformers)			
N			
Number of Services	5	C	1-2
O			
Office Locations			
Our (Definition)			
Our Service Facilities	5		
Overhead Service from	3	D	1-2
Overhead System			
P			
Phone Automatic Meter Reading	8	K.1	
Pole-Mounted Service	6	D	3
Power Factor	9	E	3
Primary Service	3	C	1
Private Property	1	E	2
R			
Recording Meter	8	K.4	
Request for Electric Service	1	B	2
Residential Cut and Reconnect Policy	2		
Removal of Service at Your Request	4	F	2

	<u>Section</u>	<u>Item</u>	<u>Page</u>
S			
Safety: The First Priority	1	A	1-2
Service: Network (Definition)			
Service: Primary (Definition)			
Service: Secondary (Definition)			
Service Drop (Definition)			
Service Entrance Conductors	6	C	2
Service Equipment	6	B	1-2
Service Facilities (Ours)	5		
Service Facilities (Yours)	6		
Service Lateral (Definition)			
Service Location (Definition)			
Service Location	6	A	1
Service Changes	1	H	5
Supply Characteristics	4	A	1-2
Self-Contained Single-Phase Meter Installations	8	H	
Self-Contained Three-Phase Meter Installations	8	I	
Sequence of Meter and Service Equipment Single-Phase	8	H.2	
Sequence of Meter and Service Equipment Three-Phase	8	I.2	
Slip Meter Riser (Definition)			
Special Request Metering	8	K.3	
Suitable Backfill (Definition)			
Swimming Pools	1	A.7	1
T			
Temporary Service	1	D	3
Third Party Communication Companies' Attachments to CL&P Distribution Facilities	7		
Tree Trimming	3	D.1.d	3
Types of Secondary Service	3	D	1-2
Two-Phase Supply	4	C	3

	<u>Section</u>	<u>Item</u>	<u>Page</u>
U			
Underground Manhole System (Definition)			
Unusual Conditions	1	B	2
Uninterruptible Power Supply	10	C	2
V			
Violations (Cut & Reconnect Policy)	2		
Voltage, Nominal	4	3	1
W			
We (Definition)		xvii	
Wiring Trough	8	H.4	
X			
X-Ray Equipment	9	A	1
Y			
You (Definition)			
Your (Definition)			

This checklist is provided as a quick reference to help you successfully complete a project.

For New Services:

Have you:

- ☐ Submitted a “Request for Electric Service” via phone, internet, mail or in person
- ☐ Obtained all local permits
- ☐ Received approval for custom, combination or instrument transformer metering equipment
- ☐ Discussed the routing and location of the service with a technician
- ☐ Discussed the need for steel sweeps in the conduit system (if applicable)
- ☐ Coordinated with other utilities
- ☐ Received an approved meter location
- ☐ Paid all applicable charges, if required
- ☐ Notified Call Before You Dig (if applicable)
- ☐ Installed service entrance equipment
- ☐ Installed an approved meter socket with optically clear cover
- ☐ For a conduit system, installed a slip joint, sweeps, conduit and ¼” pulling line
- ☐ For a conduit system where steel sweep(s) are required, install a ground to the sweep at the meter location
- ☐ Permanently marked each meter socket and load disconnect with its unique identification.
- ☐ Establish a safe work space in front of each meter location
- ☐ Called the local inspecting authority for inspection/approval.

For Service Changes

Have you:

- ☐ Confirmed that service locations and meter locations meet requirements of this booklet
- ☐ Submitted a “Request for Electric Service” via phone, internet, mail or in person
- ☐ Obtained all local permits
- ☐ Received approval for custom, combination or instrument transformer metering equipment
- ☐ Discussed the need for steel sweeps in the conduit system (if applicable)
- ☐ Received an approved meter location (if applicable)
- ☐ Paid all applicable charges, if required
- ☐ Notified Call Before You Dig (if applicable)
- ☐ Installed service entrance equipment
- ☐ Installed an approved meter socket with optically clear cover
- ☐ For a conduit system, installed a slip joint, sweeps, conduit and ¼” pulling line
- ☐ For a conduit system where steel sweep(s) are required, install a ground to the sweep at the meter location
- ☐ Permanently marked each meter socket and load disconnect with its unique identification.
- ☐ Establish a safe work space in front of each meter location
- ☐ Called the local inspecting authority for inspection/approval.

Checklist for Instrument Transformer Rated Installations

Have you:

- ☐ Barrel locked sealing device for main disconnect.
- ☐ Approved instrument transformer enclosure.
- ☐ Barrel locked sealing device for instrument transformer enclosure
- ☐ Equipment grounds must be installed.
- ☐ Approved, pre-wired combination meter socket and test switch is permanently mounted.
- ☐ Conduit installed between meter socket and CT compartment.
- ☐ If using PVC conduit, a separate bonding wire is installed according to code.
- ☐ CTs/PTs properly mounted and secured; If bar-type, CT's are properly torqued.
- ☐ CT's are located on **load side** of main switch (cold sequence) unless CL&P has granted an exception.
- ☐ A #4 Burndy lug (or equivalent) has been installed.
- ☐ for equipment (case) ground inside transformer compartment.
- ☐ for neutral connection in transformer cabinet, wired to neutral bus
- ☐ on each phase bus, line side of CT (window-type CTs)

When all the above items have been completed, call local CL&P office to schedule wiring.

Please consult CL&P's Information and Requirements booklet (Section 7 for information on Instrument Transformer Metering Requirements.

NOTES:

ELECTRICAL CONTRACTORS

Your “Service Requests” are only a >CLICK< away!

Quick and Easy * Self Serve * Convenient and Secure

Electrical Contractors are in control with CL&P's online Request for Electric Service system. Contractors can initiate, submit and monitor the status of a particular request for CL&P electric service, anytime, at www.cl-p.com.

Each electric service request is assigned a unique identification number allowing you to monitor the progress of each service requests. You can:

- View CL&P's planned scheduled date.
- View the status on job requirements such as municipal inspection approvals and easements.
- Identify the CL&P Job Designer assigned to the request.
- Access all of your requests for electric service 24/7.

Registering is free and easy.

1. Visit “For My Business” on www.cl-p.com.
2. Click on Service Request for Contractors
3. Follow instruction on “How to Register”.

Request for Electric

www.cl-p.com

For assistance or more information, call CL&P's New Service Clearing Desk at 1-888-LIGHTCO (1-888-544-4826) or email us at:

CL&PSVC@NU.com

To contact us:

Call toll-free **1-800-286-2000** or from the Hartford Exchange, call **860-947-2000**

Ask for the “New Service Job Designer” in the appropriate CL&P office.

A directory of Job Designers, sorted by town assignment, is provided for registered contractors at our website:
www.cl-p.com

To electronically submit a CL&P “Service Request”, visit our website:
www.cl-p.com

To create or inquire about a CL&P “Service Request”, contact the CL&P Clearing Desk.

Call toll-free: **1-888-544-4826**

Fax toll-free: **1-877-285-4448**

Contact us via email: ***clpsvc@nu.com***

“CALL BEFORE YOU DIG”
CONNECTICUT: **1-800-922-4455**

This booklet is available online at ***www.cl-p.com***



**Connecticut
Light & Power**

The Northeast Utilities System

To contact us:

Call toll-free **1-800-286-2000** or from the Hartford Exchange, call **860-947-2000**

Ask for the “New Service Job Designer” in the appropriate CL&P office.

A directory of Job Designers, sorted by town assignment, is provided for registered contractors at our website:
www.cl-p.com

To electronically submit a CL&P “Service Request”, visit our website:
www.cl-p.com

To create or inquire about a CL&P “Service Request”, contact the CL&P Clearing Desk.

Call toll-free: **1-888-544-4826**

Fax toll-free: **1-877-285-4448**

Contact us via email: ***clpsvc@nu.com***

“CALL BEFORE YOU DIG”
CONNECTICUT: **1-800-922-4455**

This booklet is available online at ***www.cl-p.com***



**Connecticut
Light & Power**

The Northeast Utilities System